Configuration Code HB01 General-Purpose Connection Heads and Options

The general-purpose, screw-cover connection heads listed below meet NEMA requirements for indoor or outdoor use providing protection against dust, rain, splashing and hose-directed water. These connection heads have easy access, one-turn caps; accept Pyromation 300 series and DIN terminal blocks and transmitters, and provides greater volume for ease of field wiring. Please refer to page AC-5 & 6 for additional head descriptions and complete specifications.



ORDER COD


1-1

31C

1-2

GS-OR

Example Order Number:



1-1 General-Purpose Cast Iron
DESCRIPTION

Conduit

Opening

3/4" NPT

3/4" NPT

3/4" NPT

Standard

Gasket

Graphite

Graphite

Graphite

Process

Opening

1/2" NPT

3/4" NPT

1" NPT

1-1 General-Purpose 316 Stainless Steel

ORDER CODE	DESCRIPTION			
	Process Opening	Conduit Opening	Standard Gasket	
91C	1/2" NPT	3/4" NPT	Graphite	
91D	3/4" NPT	3/4" NPT	Graphite	

-1-1 General-Purpose White Polypropolyene

ORDER CODE	DESCRIPTION			
	Process Opening	Conduit Opening	Standard Gasket	
63C	1/2" NPT	3/4" NPT	Buna N O-ring	

1-2 Head Options

1 - 3

343-3

ORDER CODE	DESCRIPTION			
W [1]	White epoxy coating			
PS	Process set screw			
GS	Internal ground screw			
OR	Buna N O-ring			
HS	Security screw			
[1] Only available on 21C				

[1] Only available on 31C

1-3 Terminal Blocks					
ORDER CODE	DESCRIPTION	CONDUCTOR SIZE			
341	Single terminal block	Up to 8 AWG			
342	Duplex terminal block	Up to 8 AWG			
343-2	Triplex terminal block with 2 brass terminals	Up to 12 AWG			
343-3	Triplex terminal block with 3 brass terminals	Up to 12 AWG			
343-4	Triplex terminal block with 4 brass terminals	Up to 12 AWG			
343-6	Triplex terminal block with 6 brass terminals	Up to 12 AWG			
Defer to page AC 4 for block appointions					

Refer to page AC-4 for block specifications.

© 2006 Pyromation, Inc.



ORDER

CODE

34C

34D

34E