

**PELICAN™**

# 2740 LED

## Instructions

### Main White

- **-High> Low> Flashing> Off**
- Press once for high mode.
- To go to low mode from high, press switch again within 1 second.
- To go to flashing mode from low mode, press switch again within 1 second.
- To turn off, press switch after 1 second of previous switch activation.

To toggle between white and red: Press and hold for more than 1 second (anytime while the light is in any mode or off).

### Red

- **-On> Flashing> Off**
- Press once for on.
- To go to flashing mode, press switch again within 1 second.
- To turn off, press switch after 1 second of previous switch activation.

---

### Battery Replacement

1. Open the battery cover.
2. Remove old batteries (dispose of properly) and replace with three 1.5V AAA size alkaline batteries according to the polarity label.
3. Close the battery cover.

---

### Battery Safety Information

**WARNING: HANDLE AND STORE BATTERIES PROPERLY TO AVOID INJURY OR DAMAGE. BATTERIES CAN BE DANGEROUS!**

Most battery issues arise from improper handling of batteries, and particularly from the use of damaged or counterfeit batteries. Please review the information below to avoid serious injury and/or damage to your property.

#### Alkaline Batteries

1. For those lights with hazardous location safety approvals for explosive environments please be advised that the safety approval is only valid for the specified battery type manufacturer and, where applicable, brand names that are displayed on the flashlight and/or instructions sheets that are supplied with the light. The use of other battery technologies may reduce the performance of the flashlight and will invalidate the safety approval.
2. Always read the battery manufacturers recommendations for the appropriate use of the battery technology/brand prior to using the flashlight.
3. When replacing the batteries:
  - a. Replace all the batteries at the same time.
  - b. Do not mix battery brands and old and new batteries.
  - c. Always insert batteries correctly with regard to polarity (+ and -) marked on the battery and equipment.
4. Do not change batteries in a hazardous location.
5. Remove batteries from equipment if it is not to be used for an extended period of time.

12/11