

## Universal IAQ instrument

testo 400 - the multitasker  
for IAQ professionals

---

Measures all IAQ-related parameters: Flow, temperature, humidity, pressure, illuminance, radiant heat, turbulence, CO<sub>2</sub> and CO

---

High-precision, location-independent and integrated differential pressure sensor

---

High-quality digital probes and an intelligent calibration concept


---

Document measuring values directly on the customer's site and send them by e-mail, or further analyze them using the testo DataControl PC software

---

Smart and intuitive measurement programs:

- HVAC grid measurement in accordance with EN ISO 12599 and ASHRAE 111
  - PMV/PPD in accordance with EN ISO 7730 and ASHRAE 55
  - Draught and degree of turbulence in accordance with EN ISO 7730 and ASHRAE 55
  - WBGT measurement in line with DIN 33403 and EN ISO 7243, NET measurement in accordance with DIN 33403
- 



Compatible with a comprehensive selection of Bluetooth® and cable probes.



testo 400 is the universal measuring instrument for all IAQ professionals, enabling them to measure, document and analyze all IAQ parameters with just one instrument. Your benefits:

- Smart support through stored measurement menus and evaluation of measuring values according to the traffic light principle – for error-free measurements
- Manage all the relevant customer data, including measuring points, directly in the instrument - work directly and efficiently on site
- Complete and send measuring values with full documen-

- Probe heads can be changed without restarting the instrument – easy handling with no lost time
- Calibration of probes which is independent of the measuring instrument and adjustment function at up to six measuring points for zero-error display – fewer downtimes and high-precision measurements

As consultants, experts, technical service providers or service technicians in the air conditioning and ventilation sector, the testo 400 therefore supports you in the truly smart performance of your measuring tasks. Relevant quality parameters in industrial production and manufacturing pro-

## Technical data

Differential pressure (integrated)	
Measuring range	-100 to +200 hPa
Accuracy ( $\pm 1$ digit)	$\pm(0.3 \text{ Pa} \pm 1\% \text{ of m.v.})$ (0 to 25 hPa) $\pm(0.1 \text{ hPa} + 1.5\% \text{ of m.v.})$ (25.001 to 200 hPa)
Resolution	0.001 hPa
Absolute pressure (integrated)	
Measuring range	700 to +1100 hPa
Accuracy ( $\pm 1$ digit)	$\pm 3 \text{ hPa}$
Resolution	0.1 hPa
Temperature NTC (with appropriate probe)	
Measuring range	-40 to +150 °C
Accuracy ( $\pm 1$ digit)	$\pm 0.2 \text{ °C}$ (-25 to 74.9 °C) $\pm 0.4 \text{ °C}$ (-40 to -25.1 °C) $\pm 0.4 \text{ °C}$ (+75 to +99.9 °C) $\pm 0.5\% \text{ of m.v. (remaining meas. range)}$
Resolution	0.1 °C
Temperature TC type K (with appropriate probe)	
Measuring range	-200 to +1370 °C
Accuracy ( $\pm 1$ digit)	$\pm(0.3 \text{ °C} + 0.1\% \text{ of m.v.})$
Resolution	0.1 °C

General technical data	
Probe connections	4x Bluetooth®, 2x TUC*, 2x TC type K
Interfaces	Bluetooth®, WLAN, USB
Operating temperature	-5 to +45 °C
Storage temperature	-20 to +60 °C
Power supply	Rechargeable li-ion battery (5550 mAh)
Battery life	approx. 10 hrs continuous operation
Display	5.0 inch HD touch display 1280 x 720 px resolution
Camera	Main camera: 8.0 MP Front camera: 5.0 MP
Memory	2 GB (corresponds to approx. 1,000,000 readings)
Protection class	IP40
Dimensions	210 x 95 x 39 mm
Weight	510 g

\*TUC connection (Testo Universal Connector): For the connection of fixed cable digital probes and NTC probes.

## Ordering data

**testo 400**

testo 400 universal IAQ instrument, including transport case for volume flow measurement, testo DataControl software, connection hose, mains unit with USB cable and calibration protocol.



Order no. 0560 0400

**IAQ data logger**

IAQ data logger for long-term measurements with the testo 400 including mains unit with USB cable and calibration protocol.



Order no. 0577 0400

## Ordering data for kits

### testo 400 air flow kit with hot wire probe

- testo 400 universal IAQ instrument, including transport case for volume flow measurement, testo DataControl software, silicone hoses, mains unit with USB cable and calibration protocol
- Hot wire probe with Bluetooth®, including temperature and humidity sensor (comprising hot wire probe head, telescope (extendable to 1.0 m) handle adapter and Bluetooth® handle), 4 x AA batteries and calibration protocol
- Vane probe head (Ø 100 mm), including temperature sensor and calibration protocol
- High-precision humidity/temperature probe head, including calibration protocol
- 90° angle for connecting vane probes (Ø 100 mm)

Order no. 0563 0400 71



### testo 400 air flow kit with 16 mm vane probe

- testo 400 universal IAQ instrument, including transport case for volume flow measurement, testo DataControl software, silicone hoses, mains unit with USB cable and calibration protocol
- Vane probe (Ø 16 mm) with Bluetooth®, including temperature sensor (comprising 16 mm vane probe head, telescope (extendable to 1.0 m), handle adapter and Bluetooth® handle), 4 x AA batteries and calibration protocol
- Vane probe head (Ø 100 mm), including temperature sensor and calibration protocol
- High-precision humidity/temperature probe head, including calibration protocol
- 90° angle for connecting vane probes (Ø 100 mm)

Order no. 0563 0400 72












### testo 400 IAQ and comfort kit with tripod







- testo 400 universal IAQ instrument, testo DataControl software, silicone hoses, mains unit with USB cable and calibration protocol
- CO<sub>2</sub> probe with Bluetooth®, including temperature and humidity sensor, (comprising CO<sub>2</sub> probe head and Bluetooth® handle), 4 x AA batteries, table stand and calibration protocol
- Turbulence probe with fixed cable, including calibration protocol
- Globe thermometer Ø 150 mm with fixed cable, TC type K, for measuring radiant heat
- Measuring tripod for comfort level measurement, consisting of folding stand, mounting rod, 4 x probe mounts, including bag
- testo 400 transport case for comfort level measurement



# Digital flow probes



















Probe type		Measuring range	Accuracy	Resolution	Order no.
<b>Digital flow probes</b>					
Hot wire probe with Bluetooth®, including temperature and humidity sensor		0 to 50 m/s -20 to +70 °C 5 to 95 %RH 700 to 1100 hPa	±(0.03 m/s + 4% of m.v.) (0 to 20 m/s) ±(0.5 m/s + 5% of m.v.) (20.01 to 30 m/s) ±0.5 °C (0 to +70 °C) ±0.8 °C (-20 to 0 °C) ±3.0 %RH (10 to 35 %RH) <sup>3)</sup> ±2.0 %RH (35 to 65 %RH) <sup>3)</sup> ±3.0 %RH (65 to 90 %RH) <sup>3)</sup> ±5 %RH (remaining meas. range) <sup>3)</sup> ±3 hPa	0.01 m/s 0.1 °C 0.1 %RH 0.1 hPa	0635 1571
Hot wire probe, fixed cable, including temperature and humidity sensor					0635 1572
Hot wire probe head, including temperature and humidity sensor					0635 1570
Vane probe (Ø 16 mm) with Bluetooth®, including temperature sensor		0.6 to 50 m/s -10 to +70 °C	±(0.2 m/s + 1% of m.v.) (0.6 to 40 m/s) ±(0.2 m/s + 2% of m.v.) (40.1 to 50 m/s) ±1.8 °C	0.1 m/s 0.1 °C	0635 9571
Vane probe (Ø 16 mm), fixed cable, including temperature sensor					0635 9572
Vane probe head (Ø 16 mm), including temperature sensor					0635 9570
Hot wire probe, fixed cable, including temperature sensor		0 to 30 m/s -20 to +70 °C 700 to 1100 hPa	±(0.03 m/s + 4% of m.v.) (0 to 20 m/s) ±(0.5 m/s + 5% of m.v.) (20.01 to 30 m/s) ±0.5 °C ±3 hPa	0.01 m/s 0.1 °C 0.1 hPa	0635 1032
Vane probe (Ø 16 mm), fixed cable		0.6 to 50 m/s	±(0.2 m/s + 1% of m.v.) (0.6 to 40 m/s) ±(0.2 m/s + 2% of m.v.) (40.1 to 50 m/s)	0.1 m/s	0635 9532
Fume cupboard probe, fixed cable		0 to 5 m/s 0 to +50 °C 700 to 1100 hPa	±(0.02 m/s + 5% of m.v.) (0 to 5 m/s) ±0.5 °C ±3 hPa	0.01 m/s 0.1 °C 0.1 hPa	0635 1052

**We recommend the extension kit (0554 0990) for measuring flows in ducts with a large cross-section. This enables the telescope to be extended to up to 2 m for all flow probes with an interchangeable handle.**

High-precision vane probe (Ø 100 mm) with Bluetooth®, including temperature sensor		0.1 to 15 m/s -20 to +70 °C	±(0.1 m/s + 1.5% of m.v.) (0.1 to 15 m/s) ±0.5 °C	0.01 m/s 0.1 °C	0635 9371
High-precision vane probe (Ø 100 mm), fixed cable, including temperature sensor					0635 9372
High-precision vane probe head (Ø 100 mm), including temperature sensor					0635 9370
Vane probe (Ø 100 mm) with Bluetooth®, including temperature sensor		0.3 to 35 m/s -20 to +70 °C	±(0.1 m/s + 1.5% of m.v.) (0.3 to 20 m/s) ±(0.2 m/s + 1.5% of m.v.) (20.01 to 35 m/s) ±0.5 °C	0.01 m/s 0.1 °C	0635 9431
Vane probe (Ø 100 mm), fixed cable, including temperature sensor					0635 9432
Vane probe head (Ø 100 mm), including temperature sensor					0635 9430

**The telescope with 90° angle (0550 0960) has been developed for convenient ceiling measurements. It can easily be fitted onto the 100 mm vane probes.**

# Other digital probes and probe accessories






Probe type		Measuring range	Accuracy	Resolution	Order no.
<b>Digital humidity probes</b>					
Humidity/temperature probe with Bluetooth®		0 to 100 %RH -20 to +70 °C	±2 %RH (5 to 90 %RH) <sup>3)</sup> ±0.5 °C	0.1 %RH 0.1 °C	0636 9731
Humidity/temperature probe, fixed cable					0636 9732
Humidity/temperature probe head					0636 9730
High-precision humidity/temperature probe with Bluetooth®		0 to 100 %RH -20 to +70 °C	±(0.6 %RH + 0.7% of m.v.) (0 to 90 %RH) <sup>3)</sup> ±(1.0 %RH + 0.7% of m.v.) (90 to 100 %RH) <sup>3)</sup> ±0.3 °C (15 to 30 °C) ±0.5 °C (remaining meas. range)	0.01 %RH 0.1 °C	0636 9771
High-precision humidity/temperature probe, fixed cable					0636 9772
High-precision humidity/temperature probe head					0636 9770
Robust humidity/temperature probe for temperatures up to +180 °C, fixed cable		0 to 100 %RH -20 to +180 °C	±3 %RH (0 to 2 %RH) <sup>3)</sup> ±2 %RH (2.1 to 98 %RH) <sup>3)</sup> ±3 %RH (98.1 to 100 %RH) <sup>3)</sup> ±0.5 °C (-20 to 0 °C) ±0.4 °C (0.1 to +50 °C) ±0.5 °C (+50.1 to +180 °C)	0.1 %RH 0.1 °C	0636 9775
<b>Digital comfort probes</b>					
Turbulence probe, fixed cable		0 to +5 m/s 0 to +50 °C 700 to 1100 hPa	±(0.03 m/s + 4% of m.v.) (0 to 5 m/s) ±0.5 °C ±3 hPa	0.01 m/s 0.1 °C 0.1 hPa	0628 0152
Lux probe, fixed cable		0 to 100,000 lux	DIN 13032-1 Appendix B Class C according to DIN 5032-7	0.1 lux (< 10,000 lux) 1 lux (≥ 10,000 lux)	0635 0551
CO <sub>2</sub> probe with Bluetooth®, including temperature and humidity sensor		0 to 10,000 ppm CO <sub>2</sub> 5 to 95 %RH 0 to +50 °C 700 to 1100 hPa	±(50 ppm + 3% of m.v.) (0 to 5,000 ppm) ±(100 ppm + 5% of m.v.) (5,001 to 10,000 ppm) ±3 %RH (10 to 35 %RH) <sup>3)</sup> ±2 %RH (35 to 65 %RH) <sup>3)</sup> ±3 %RH (65 to 90 %RH) <sup>3)</sup> ±5 %RH (remaining meas. range) <sup>3)</sup> ±0.5 °C ±3 hPa	1 ppm 0.1 %RH 0.1 °C 0.1 hPa	0632 1551
CO <sub>2</sub> probe, fixed cable, including temperature and humidity sensor					0632 1552
CO <sub>2</sub> probe head, including temperature and humidity sensor					0632 1550
CO probe with Bluetooth®		0 to 100 ppm  100.1 to 500 ppm	±3 ppm (0 to 30 ppm) ±5 ppm (30.1 to 100 ppm)  ±10 % of m.v. (100.1 ... 500 ppm)	0.1 ppm	0632 1271
CO probe, fixed cable					0632 1272
CO probe head					0632 1270
<b>Probe handles and adapters</b>					
Bluetooth® handle for connecting testo 400 testo 440 probe heads					0554 1111
Cable handle for connecting testo 400 / testo 440 probe heads					0554 2222
Handle adapter for connecting testo 400 / testo 440 flow probes					0554 2160

# Testo Smart Probes














Testo Smart Probes		Measuring range	Accuracy $\pm 1$ digit	Resolution	Order no.
<b>Temperature</b>					
<b>testo 115i</b> Clamp thermometer with smartphone operation, for measurements on pipelines with diameters of 6 to max. 35 mm, including batteries and calibration protocol		-40 to +150 °C	$\pm 1.3$ °C (-20 to +85 °C)	0.1 °C	0560 1115
<b>testo 905i</b> Thermometer with smartphone operation, including batteries and calibration protocol		-50 to +150 °C	$\pm 1$ °C	0.1 °C	0560 1905
<b>testo 805i</b> Infrared thermometer with smartphone operation, including batteries and calibration protocol		-30 to +250 °C	$\pm 1.5$ °C or $\pm 1.5\%$ of m.v. (0 to +250 °C) $\pm 2.0$ °C (-20 to -0.1 °C) $\pm 2.5$ °C (-30 to -20.1 °C)	0.1 °C	0560 1805
<b>Humidity</b>					
<b>testo 605i</b> Thermohygrometer with smartphone operation, including batteries and calibration protocol		0 to 100 %RH -20 to +60 °C	$\pm (1.8\%RH + 3\%$ of m.v.) at +25 °C (5 to 80 %RH) <sup>3)</sup> $\pm 0.8$ °C (-20 to 0 °C) $\pm 0.5$ °C (0 to +60 °C)	0.1 %RH 0.1 °C	0560 1605
<b>Flow</b>					
<b>testo 405i</b> Thermal anemometer with smartphone operation, telescopic tube extendable to up to 400 mm, including batteries and calibration protocol		0 to 30 m/s -20 to +60 °C	$\pm (0.1$ m/s + 5% of m.v.) (0 to 2 m/s) $\pm (0.3$ m/s + 5% of m.v.) (2 to 15 m/s) $\pm 0.5$ °C	0.01 m/s 0.1 °C	0560 1405
<b>testo 410i</b> Vane anemometer with smartphone operation, including batteries and calibration protocol		0.4 to 30 m/s -20 to +60 °C	$\pm (0.2$ m/s + 2% of m.v.) (0.4 to 20 m/s) $\pm 0.5$ °C	0.1 m/s 0.1 °C	0560 1410
<b>Pressure</b>					
<b>testo 510i</b> Differential pressure measuring instrument with smartphone operation, including hose kit (Ø 4 mm and 5 mm) with adapter, batteries and calibration protocol		-150 to 150 hPa	$\pm 0.05$ hPa (0 to 1 hPa) $\pm (0.2$ hPa + 1.5% of m.v.) (1 to 150 hPa)	0.01 hPa	0560 1510
<b>testo 549i</b> High-pressure measuring instrument with smartphone operation, including batteries and calibration protocol		-1 to 60 bar	0.5% of final value	0.01 bar	0560 1549

<sup>3)</sup> Please see the additional accuracy information for humidity in the instruction manual.

## Digital temperature probes

Probe type		Measuring range	Accuracy	Resolution	Order no.
<b>Digital temperature probes</b>					
<b>High-precision digital Pt100 penetration probe</b> for measurements in liquids and pastes with an accuracy of up to $\pm 0.05$ °C		-80 to +300 °C	$\pm 0.3$ °C (-80 to -40.001 °C) $\pm (0.1$ °C + 0.05% of m.v.) (-40 to -0.001 °C) $\pm 0.05$ °C (0 to +100 °C) $\pm (0.05$ °C + 0.05% of m.v.) (+100.001 to +300 °C)	0.001 °C	0618 0275
<b>Digital Pt100 penetration probe</b> for measurements in liquids and pastes		-100 to +400 °C	$\pm (0.15$ °C + 0.2% of m.v.) (-100 to -0.01 °C) $\pm (0.15$ °C + 0.05% of m.v.) (0 to +100 °C) $\pm (0.15$ °C + 0.2% of m.v.) (+100.01 to +350 °C) $\pm (0.5$ °C + 0.5% of m.v.) (+350.01 to +400 °C)	0.01 °C	0618 0073
<b>Glass-coated digital Pt100 laboratory probe</b> for measurements in corrosive media		-50 to +400 °C	$\pm (0.3$ °C + 0.3% of m.v.) (-50 to +300 °C) $\pm (0.4$ °C + 0.6% of m.v.) (+300.01 to +400 °C)	0.01 °C	0618 7072
<b>Robust, fast-reaction, digital Pt100 air probe</b>		-100 to +400 °C	$\pm (0.15$ °C + 0.2% of m.v.) (-100 to -0.01 °C) $\pm (0.15$ °C + 0.05% of m.v.) (0 to +100 °C) $\pm (0.15$ °C + 0.2% of m.v.) (+100.01 to +350 °C) $\pm (0.5$ °C + 0.5% of m.v.) (+350.01 to +400 °C)	0.01 °C	0618 0072
<b>Flexible digital Pt100 temperature probe</b> for measurements in locations that are difficult to access and in liquids		-100 to +265 °C	$\pm (0.3$ °C + 0.3% of m.v.)	0.01 °C	0618 0071

# Analog temperature probe

Probe type	Probe shaft/probe shaft tip dimensions	Measuring range	Accuracy	Response time	Order no.
Pipe wrap probe (NTC) for pipe diameters of 5 to 65 mm, fixed cable 1.2 m		-50 to +120 °C	±0.2 °C (-25 to +80 °C)		0615 5605
Temperature probe with Velcro (NTC), fixed cable 1.4 m	 300 mm 30 mm	-50 to +70 °C	±0.2 °C (-25 to +70 °C) ±0.4 °C (-50 to -25.1 °C)	60 s	0615 4611
Watertight immersion/penetration probe NTC, fixed cable 1.2 m	 115 mm 50 mm Ø 5 mm Ø 4 mm	-50 to +150 °C	±0.5% of m.v. (+100 to +150 °C) ±0.2 °C (-25 to +74.9 °C) ±0.4 °C (remaining meas. range)	10 s	0615 1212
Robust air probe NTC, fixed cable 1.2 m	 115 mm 50 mm Ø 5 mm Ø 4 mm	-50 to +125 °C	±0.2 °C (-25 to +80 °C) ±0.4 °C (remaining meas. range)	60 s	0615 1712
Clamp probe for measurements on pipes from 6 to 35 mm diameter, NTC, fixed cable 1.5 m		-40 to +125 °C	±1 °C (-20 to +85 °C)	60 s	0615 5505
Robust air probe, TC type K, fixed cable	 115 mm Ø 4 mm	-60 to +400 °C	Class 2 <sup>1)</sup>	200 sec	0602 1793
Very fast-reaction surface probe with sprung thermocouple strip, also suitable for uneven surfaces, measuring range briefly up to +500 °C, TC type K, fixed cable	 115 mm Ø 5 mm Ø 12 mm	-60 to +300 °C	Class 2 <sup>1)</sup>	3 sec	0602 0393
Fast-reaction paddle surface probe, for measurements in places that are difficult to access, e.g. narrow openings and cracks, TC type K, fixed cable	 145 mm 40 mm Ø 8 mm Ø 7 mm	0 to +300 °C	Class 2 <sup>1)</sup>	5 sec	0602 0193
Precise, watertight surface probe with small measuring head for even surfaces, TC type K, fixed cable	 150 mm Ø 2.5 mm Ø 4 mm	-60 to +1000 °C	Class 1 <sup>1)</sup>	20 sec	0602 0693
Very fast-reaction surface probe with sprung thermocouple strip, angled for uneven surfaces as well, measuring range briefly up to +500 °C, TC type K, fixed cable	 80 mm 50 mm Ø 5 mm Ø 12 mm	-60 to +300 °C	Class 2 <sup>1)</sup>	3 sec	0602 0993
Surface temperature probe TC type K, with telescope max. 985 mm, for measurements in locations that are difficult to access, fixed cable 1.6 m (correspondingly shorter when telescope is extended)	 985 ±5 mm 12 mm Ø 25 mm	-50 to +250 °C	Class 2 <sup>1)</sup>	3 sec	0602 2394
Magnetic probe, adhesive power approx. 20 N, with adhesive magnets, for measurements on metal surfaces, TC type K, fixed cable	 35 mm Ø 20 mm	-50 to +170 °C	Class 2 <sup>1)</sup>	150 sec	0602 4792
Magnetic probe, adhesive power approx. 10 N, with adhesive magnets, for measurements on metal surfaces, TC type K, fixed cable	 75 mm Ø 21 mm	-50 to +400 °C	Class 2 <sup>1)</sup>		0602 4892

<sup>1)</sup> According to standard EN 60584-2, the accuracy of Class 1 refers to -40 to +1000 °C (type K), of Class 2 to -40 to +1200 °C (type K) and of Class 3 to -200 to +40 °C (type K). A probe only ever complies with one accuracy class.

## Information about surface measurement:














1.800.561.8187

www.itm.com

information@itm.com







# Analog temperature probe

Probe type	Probe shaft/probe shaft tip dimensions	Measuring range	Accuracy	t <sub>99</sub>	Order no.
Watertight surface probe with wider measuring tip for even surfaces, TC type K, fixed cable		-60 to +400 °C	Class 2 <sup>1)</sup>	30 sec	0602 1993
Pipe wrap probe with Velcro strip, for measuring temperatures on pipes with diameters up to max. 120 mm, Tmax +120 °C, TC type K, fixed cable		-50 to +120 °C	Class 1 <sup>1)</sup>	90 sec	0628 0020
Pipe wrap probe for pipe diameters 5 to 65 mm, with interchangeable measuring head, measuring range briefly up to +280 °C, TC type K, fixed cable		-60 to +130 °C	Class 2 <sup>1)</sup>	5 sec	0602 4592
Replacement measuring head for pipe wrap probe, TC type K		-60 to +130 °C	Class 2 <sup>1)</sup>	5 sec	0602 0092
Clamp probe for measurements on pipes, pipe diameters 15 to 25 mm (max. 1"), measuring range briefly up to +130 °C, TC type K, fixed cable		-50 to +100 °C	Class 2 <sup>1)</sup>	5 sec	0602 4692
Precise and fast immersion probe, flexible, watertight, TC type K, fixed cable		-60 to +1000 °C	Class 1 <sup>1)</sup>	2 sec	0602 0593
Ultra-fast, watertight immersion/penetration probe, TC type K, fixed cable		-60 to +800 °C	Class 1 <sup>1)</sup>	3 sec	0602 2693
Immersion measuring tip, flexible, TC type K		-200 to +1000 °C	Class 1 <sup>1)</sup>	5 sec	0602 5792
Immersion measuring tip, flexible, TC type K		-200 to +40 °C	Class 3 <sup>1)</sup>	5 sec	0602 5793
Immersion measuring tip, flexible, for measurements in air/flue gases (not suitable for measurements in smelters), TC type K		-200 to +1300 °C	Class 1 <sup>1)</sup>	4 sec	0602 5693
Watertight immersion/penetration probe, TC type K, fixed cable		-60 to +400 °C	Class 2 <sup>1)</sup>	7 sec	0602 1293
Flexible, low-mass immersion measuring tip, ideal for measurements in small volumes, such as Petri dishes, or for surface measurements (e.g. fixed with adhesive tape)	 TC type K, 2 m, FEP-insulated thermal wire, temperature-resistant up to 200 °C, oval cable with dimensions: 2.2 mm x 1.4 mm	-200 to +1000 °C	Class 1 <sup>1)</sup>	1 sec	0602 0493
Watertight food probe made of stainless steel (IP65), TC type K, fixed cable		-60 to +400 °C	Class 2 <sup>1)</sup>	7 sec	0602 2292

<sup>1)</sup> According to standard EN 60584-2, the accuracy of Class 1 refers to -40 to +1000 °C (type K), of Class 2 to -40 to +1200 °C (type K) and of Class 3 to -200 to +40 °C (type K).







# Analog probes

Probe type	Probe shaft/probe shaft tip dimensions	Measuring range	Accuracy	t <sub>99</sub>	Order no.
<b>Thermoelectric couples</b>					
Thermoelectric couple with TC plug, flexible, length 800 mm, glass fibre, TC type K	 800 mm Ø 1.5 mm	-50 to +400 °C	Class 2 <sup>1)</sup>	5 sec	0602 0644
Thermoelectric couple with TC plug, flexible, length 1500 mm, glass fibre, TC type K	 1500 mm Ø 1.5 mm	-50 to +400 °C	Class 2 <sup>1)</sup>	5 sec	0602 0645
Thermoelectric couple with TC plug, flexible, length 1500 mm, PTFE, TC type K	 1500 mm Ø 1.5 mm	-50 to +250 °C	Class 2 <sup>1)</sup>	5 sec	0602 0646
<b>Comfort probe</b>					
Globe thermometer Ø 150 mm, TC type K, for measuring radiant heat		0 to +120 °C	Class 1 <sup>1)</sup>		0602 0743













<sup>1)</sup> According to standard EN 60584-2, the accuracy of Class 1 refers to -40 to +1000 °C (type K), of Class 2 to -40 to +1200 °C (type K) and of Class 3 to -200 to +40 °C (type K). A probe only ever complies with one accuracy class.

<b>WBGT kit</b>					
WBGT (wet bulb globe temperature) kit for assessing workplaces affected by heat in line with ISO 7243 or DIN 33403-3, comprising globe, ambient temperature / wet bulb temperature probe, plug-in head cables, tripod and case		0 to +120 °C +10 to +60 °C +5 to +40 °C	±3 %RH (0 to 2 %RH) ±2 %RH (2.1 to 98 %RH) ±3 %RH (98.1 to 100 %RH) ±0.5 °C (-20 to 0 °C) ±0.4 °C (0.1 to +50 °C) ±0.5 °C (+50.1 to +180 °C)		0635 8888 ID no. 0699 7220/1

# Pitot tubes

Probe type	Probe shaft/probe shaft tip dimensions	Measuring range	Order no.
Pitot tube, length 500 mm, Ø 7 mm, stainless steel, for measuring flow velocity*	 500 mm Ø 7 mm	Measuring range 1 to 100 m/s Operating temperature 0 to +600 °C Pitot tube factor 1.0	0635 2045
Pitot tube, length 350 mm, Ø 7 mm, stainless steel, for measuring flow velocity*	 350 mm Ø 7 mm	Measuring range: 1 to 100 m/s Operating temperature: 0 to +600 °C Pitot tube factor: 1.0	0635 2145
Pitot tube, length 1000 mm, stainless steel, for measuring flow velocity*	 1000 mm Ø 7 mm	Measuring range: 1 to 100 m/s Operating temperature: 0 to +600 °C Pitot tube factor: 1.0	0635 2345
Straight Pitot tube with integrated temperature measurement, including connection hose, length 360 mm	 360 mm	Measuring range: 1 to 30 m/s Operating temperature: 0 to +600 °C Pitot tube factor: 0.67 Minimum immersion depth: 150 mm	0635 2043
Straight Pitot tube with integrated temperature measurement, including connection hose, length 500 mm	 500 mm	Measuring range: 1 to 30 m/s Operating temperature: 0 to +600 °C Pitot tube factor: 0.67 Minimum immersion depth: 150 mm	0635 2143
Straight Pitot tube with integrated temperature measurement, including connection hose, length 1000 mm	 1000 mm	Measuring range: 1 to 30 m/s Operating temperature: 0 to +600 °C Pitot tube factor: 0.67 Minimum immersion depth: 150 mm	0635 2243

## Accessories

Accessories for comfort level measurement		Order no.
	IAQ data logger for long-term measurements with the testo 400	0577 0400
	Measuring tripod for comfort level measurements with standard-compliant positioning of probes (including bag)	0554 1591
Accessories for digital flow probes		Order no.
	Extendable telescope for testo 400 / 440 flow probes (37.5 to 100 cm including 90° angle)	0554 0960
	Telescope extension (0.9 m) for testo 400 / 440 flow probes	0554 0990
	90° angle for connecting vane probes (Ø 100 mm)	0554 0991
	Handle adapter for connection to flow probes	0554 2160
Other accessories		Order no.
	Transport case for air flow measurement (520 x 410 x 160 mm)	0516 1400
	Transport case for IAQ and comfort level measurement (520 x 410 x 210 mm)	0516 2400
	testovent 417 funnel kit comprising funnel for plate outlets (Ø 200 mm) and funnel for fans (330 x 330 mm) for incoming / outgoing air	0563 4170
	testovent 417 volume flow straightener	0554 4172
	USB mains unit, including cable	0554 1106
	Connection hose, silicone, length 5 m, maximum load capacity 700 hPa (mbar)	0554 0440
	Connection hose, silicone-free for differential pressure measurement, length 5 m, maximum load capacity 700 hPa (mbar)	0554 0453
	Control and calibration kit for Testo humidity probes, saline solution with 11.3 %RH and 75.3 %RH, including adapter for Testo humidity probes	0554 0660

## Accessories

Calibration certificates	Order no.
ISO flow calibration certificate; hot wire/vane anemometer, Pitot tube; calibration points 1; 2; 5; 10 m/s	0520 0004
ISO flow calibration certificate; hot wire/vane anemometer, Pitot tube; calibration points 0.3; 0.5; 0.8; 1.5 m/s	0520 0024
ISO flow calibration certificate; hot wire/vane anemometer, Pitot tube; calibration points 5; 10; 15; 20 m/s	0520 0034
ISO flow calibration certificate; hot wire/vane anemometer, Pitot tube; selective calibration points in the 0.5 to 27 m/s range	0520 0104
DAkKS flow calibration certificate; hot wire/vane anemometer, Pitot tube; selective calibration points in the 0.1 to 27 m/s range	0520 0214
DAkKS flow calibration certificate; hot wire/vane anemometer, Pitot tube; calibration points 0.5; 1; 2; 5; 10 m/s	0520 0244
ISO pressure calibration certificate; 5 calibration points; accuracy > 0.6% of f.v.	0520 0005
ISO pressure calibration certificate; 5 calibration points; accuracy 0.1 to 0.6% of f.v.	0520 0025
DAkKS pressure calibration certificate; 5 calibration points; accuracy > 0.6% of f.v.	0520 0225
ISO humidity calibration certificate, electronic hygrometer; calibration points 11.3 %RH and 75.3 %RH at +25 °C	0520 0006
ISO humidity calibration certificate; electronic hygrometer; calibration points 11.3; 50; 75.3 %RH at +25 °C	0520 0166
DAkKS humidity calibration certificate; electronic hygrometer; calibration points 11.3 %RH and 75.3 %RH at +25 °C	0520 0206
DAkKS humidity calibration certificate; electronic hygrometer; selective calibration points 5 to 95 %RH at -18 to +70 °C	0520 0216
ISO temperature calibration certificate, for air/immersion probe, calibration points -18°C; 0 °C; +60 °C	0520 0001
ISO temperature calibration certificate for air/immersion probe, selective calibration points in the -196 to +1200 °C range	0520 0101
DAkKS temperature calibration certificate for air/immersion probe, selective calibration points in the -196 to +1000 °C range	0520 0201
DAkKS temperature calibration certificate; measuring instruments with air/immersion probe; calibration points -20 °C; 0 °C; +60 °C	0520 0211
ISO luminous intensity calibration certificate; calibration points 0; 500; 1000; 2000; 4000 lux	0520 0010
ISO luminous intensity calibration certificate; selective calibration points in the 0; 50 to 10,000 lux range	0520 0123
ISO CO <sub>2</sub> calibration certificate; CO <sub>2</sub> probes; calibration points 0; 1000; 5000 ppm	0520 0033