

# HG 2320 ESD

## Electrostatic Discharge Heat Gun

### Technical Specifications

**Voltage:** 120 VAC / 60 Hz  
**Power:** 1600 watts  
**Amps:** 13.3  
  
**Surface Conductivity:** 10<sup>4</sup> ohms  
**Airflow Rate:** 3.6 - 17.6 cfm. (continuously variable)  
**Stages:** 2 (continuously variable)  
  
**Power Cord:** Industrial grade rubber, length: 6 ft  
**Motor:** Brush motor  
**Heating Element:** Cereamic heating element  
  
**Motor Lifetime:** 1000 hours  
**Accessories:** Use of standard accessories  
**Temperature:** 120-1200° F  
**Net Weight:** 2.19 lbs  
**Dimensions:** 9.96" x 3.41" x 7.87"  
 (L x W x D)

**Single Sell Pack:** Dimensions: 10.20" x 3.54" x 9.33"  
 Weight: 2.60 lbs

**Features:** Higher durability (+20%), optimized weight balance, LCD-Display, 4 settings programmable, heat build-up warning, hanging ring, easily replaceable power cord, residual heat indicator, optional temperature scanner and fine dist filter

**Warranty:** 1 year



UPC Code	Product No.
0 18139 73503 8	110073503