



## **Technical data**

Item no. Capacity Division

Colour

Precision

Tare (zero adjustment)

Exchange of lower suspension

Standard suspension

S (Scale length)

L0 (Length without load)

Lm (Maximum length) Ø (Diameter)

Components

Net weight Gross weight Measuring position Calibration by user

Manual

Packaging

Warranty **Customs Tarif** 

20030 30 g 0.25 g red ± 0.3% ~ 20%

"click and go" system



80 mm 220 mm

300 mm

non-corroding (spring and clip only protected)

39 g

vertical

not applicable (only by manufacturer)

DE/EN/FR/IT/ES/PT/NL transparent designer

3 years

8423.8100



## **Brief product information**

Precise and handy Spring Balance with durable anodised aluminium tube and long scale of high resolution. Tare and zero adjustment. Tare screw with incremental rotation, to avoid inadvertent adjustment. Swivelable, rotatable and removable suspension bow, guided in a ring. Lower suspension swivels, rotates and can be easily changed using different accessories. A multifunctional long life measuring instrument for weighing and measuring traction forces. Always ready for use, needs no batteries. A time-tested original Swiss quality product.

## More

See Support -> Examples -> Applications. Special Micro-Line models see -> Special scales. For spare parts see -> Accessories.

## **Optional Accessories**

Further accessories e.g. to replace the lower standard suspension. See -> Accessories.

