

# 772 ARX Nitrile Long Sleeve



## Cotton/polyester material Nitrile coating

### DESCRIPTION

- Fully coated, extra coating over entire hand
- Extended sewn sleeve, elasticated border
- Rough finish over entire surface
- Antibacterial and anti-odour treatment
- Anatomical shape
- Cut and sewn
- Eyelet for ventilation and hanging



### BENEFITS

- A flexible, robust glove offering great dexterity and with good resistance to tearing
- Protects the hand from oils, hydrocarbons, grease and abrasion, with effective long lasting grip
- Impermeable for working in damp or greasy environments, enabling you to grip objects securely
- Sleeve stays correctly adjusted
- Surface provides tactile feel and better grip
- Greater hygiene
- Easy hang storage
- Designed for easy movement and continuous wear
- Extended protection for the entire arm

### RECOMMENDED FOR THESE RISKS:

Cold  
Chemicals  
Oils  
Abrasion

### RECOMMENDED FOR THESE LINES OF WORK:

Mechanical industry  
Chemical industry / Alkaline components

### AVAILABLE SIZES

8/M • 9/L • 10/XL

### LENGTH

Dependent on size, in mm (flat)

650

### PACKAGING

Pairs per pack/box

5/60

### COLOUR OF SUPPORT/COATING

Yellow

### THICKNESS

in mm

0,80

### RECOMMENDATIONS FOR USE

- Do not use with chemicals other than those tested without prior trials
- The stated impermeability performance level (EN374-3) does not reflect the actual protection level at the place of work – other factors may influence the performance.
- Store away from light and humidity
- Rinse the gloves in running water before removing, using a neutral detergent if necessary



ABRASION 0 1 2 3 4  
CUTTING 0 1 2 3 4 5  
TEARING 0 1 2 3 4  
PUNCTURE 0 1 2 3 4



METHANOL 0 1 2 3 4 5 6  
N-HEPTANE 0 1 2 3 4 5 6  
HYDROCHLOR. ACID 36% X 1 2 3 4 5 6

D - DICHLOROMETHAN 0 1 2 3 4 5 6  
CAUSTIC SODA 40% 0 1 2 3 4 5 6  
KEROSENE X 1 2 3 4 5 6

F - TOLUENE 0 1 2 3 4 5 6  
SULPHURIC ACID 96% 0 1 2 3 4 5 6

[ Updated 01/02/2010 ]



The Ultimate in Comfort and Dexterity

information@itm.com

1.800.561.8187

www.itm.com