Leica NA300 Series Unique. Accurate. Simple.

Professionals face many obstructions on site. Whatever the levelling challenge, Leica NA300 Series levels overcome. Rely on the known expertise of Leica Geosystems for the best quality and performance. On your terms, on your site, Leica Geosystems and the Leica NA300 Series are your trusted partners for accurate measurements every time.

UNIQUE. ACCURATE. SIMPLE.

- Distinctive design and proven technology, inside and out
- Leica Geosystems understands construction and provides levels for all needs
- Protected shape for increased ergonomic handling while ensuring the highest quality results
- Simple handling for quick and accurate measurements



KEY BENEFITS

- Quick and easy measurements
- Unique design and highest quality of results for levelling needs
- Manufactured for the most rugged sites and the harshest conditions
- Expert knowledge of Leica Geosystems with more than 270 service centres worldwide
- Unbeaten service offering







Leica NA300 Series

	Leica NA320	Leica NA324	Leica NA332
TECHNICAL DATA			
TECHNICAL DATA Standard deviation for 1 km double levelling (ISO17123-2) TELESCOPE	2.5 mm	2.0 mm	1.8 mm
Telescope image		Upright	
Magnification	20 x	24 x	32 x
Objective aperture		36 mm	
Shortest target distance from instr. axis		<1.0 m	
Field of view at 100 m		<2.1 m	
Multiplication factor		100	
Additive constant		0	
COMPENSATOR			
Working range		± 15′	
Setting accuracy (standard deviation)		<0.5''	
Sensitivity		8'/2 mm	
HORIZONTAL CIRCLE			
Graduation		360°	
Graduation interval		1°	
Weight (net)		1.5 kg	
Operating temperature range		–20° C to +40° C	



Leica Geosystems offers a wide variety of construction instruments for your everyday use. Contact your local Leica Geosystems dealer for more information on our solutions.



Digital Levels



Construction Lasers





Cable Locators

_ _ _ _ _ _

Pipe Lasers





