

Traceable® Water-Resistant Thermometer

Waterproof case, cable, and stainless-steel probe monitors temperatures in any wet area

Traceable® Shock/Water-Resistant unit delivers reading updates every second

- Water/shockproof case provides flawless readings in freezers, water baths, incubators, tanks
- Stainless-steel probe efficiently monitors temperatures in liquids, semi-solids, air/gases
- Wide range covers 99 percent of the lab's routine temperature measurements

Features:

- Water-resistant and Shock-resistant
- One-key operation recalls MIN/MAX temperature results
- °F/°C switchable
- Bright ¼-inch-high display is easy to view
- Individually serialized, calibrated, and certified Traceable® to NIST

Additional features:

- Suction cups allow for affixing probe to the side of a tank, water bath, or anything with a smooth surface
- Probe: 0.14" diameter, 5" length
- Cable: water-resistant 120"
- Case is high-impact, chemical-resistant ABS plastic



Traceable to NIST for accuracy

Multi-point calibration on an individually-numbered Traceable® Certificate which assures accuracy from our ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability of measurements to the SI units through NIST or other recognized national measurement institutes (NMI) that are signatories to the CIPM Mutual Recognition Agreement.

Cat. No. 4039 Traceable® Water-Resistant Thermometer

Cat. No. 4339 Traceable® Ultra™ Water-Resistant Thermometer

Product Specifications

- ▶ **Range:** -50 to 300°C (-58 to 572°F)
- ▶ **Resolution:** 0.1° from -19.9 to 199.9°C; otherwise 1°C
- 4039—**
 - ▶ **Accuracy:** ±1°C between -20 and 100°C
- 4339—**
 - ▶ **Accuracy:** ±0.5°C at tested points
 - ▶ **Probe:** 0.14" diameter, 5" probe length, 120" cable
 - ▶ **Dimensions:** 1¾ dia. x ½" depth
 - ▶ **Weight:** 2 ounces
 - ▶ **Supplied:** battery, probe, cable, suction cups, magnet, Velcro® strips, Traceable® Certificate



1.800.561.8187

www.itm.com

information@itm.com