

TEMPEST™ TIC 4.3



High Resolution Thermal imaging camera

Efficient and versatile = 3 buttons + 4" display

Particularly suitable for the First attack. TEMPEST TIC 4.3 offers unbeatable value and best quality, combined with all important features: ideal for firefighting, first attack, search for missing persons and fire...




Outstanding features:

- Compact 6.9 x 5.7 x 3.8"
- Lightweight 2.09lbs with 2 batteries and side straps.
- Large 4" display for detailed visibility
- Widest detection range: -40 °F to +2100 °F
- Video recording, picture capture and image freeze
- Batteries: 6 year warranty, 5000 charging cycles
- Safe batteries (LiFePO4): for high temp operations
- With ECO BOOST System for extended running time
- Up to 8h running time (2 batteries) with Eco-Boost-System (up to 60% additional running time than previous model)
- Removable Pistol grip option
- · Boot time: less than 5 sec
- 3 Large buttons: easy to operate even with gloves
- Functions:
 - o ON/OFF
 - o Zoom x2 x4
 - Colorization selection (3 or 5 modes)
 - Image freeze / picture capture (option)
 - Video recording (option)
 - Replay picture and video on screen
 - Laser pointer (option)




Color schemes:

TEMPEST TIC 4.3 offers **3 color schemes** as standard: **Fire, Search, and Inverse**+2 colur schemes as option: **Cold Finder and Multicolor**




STD / FIRE:
Dark Red >1560°F
Red > 1250°F
Orange > 930°F
Dark Yellow >660°F
Yellow > 400°F
White = Hot
Black = cold




SEARCH: 2 hottest % colored in Red and the 5 following hottest % in Yellow-Orange.



COLD Finder: Blue color for coldest areas



INVERSE: Same as Fire scheme but White & Black are inversed: White = Cold Black = Hot



MULTICOLOR: For Industrial applications

3 Sensitivity modes with automatic switch according observed scene:

-High sensitivity temperature range: -40 +300 °F -Medium sensitivity temperature range: -40 + 950 °F





Characteristics:

Tempest TIC	4.3 with Eco-Boost-System				
Dimensions	L6.9 x W5.7 x H3.8" (H = $+4.3$ " with optional pistol grip)				
Weight	2.09lbs with 2 batt / 1.91lbs with 1 bat (+0.37lbs with optional pistol grip)				
Display	4" LCD / 320 x 240 (76.800) px / Backlighted / Brightness: 74.32 cd/ft²				
Frequency	60Hz Fps				
T℃ Range	-40° to +2100°F				
Colorization	Std: Fire, Search, Inverse Option: Cold finder and Multicolor				
Housing					
Material	PUR / Elastomer				
Drop Test	6.5 ft on concrete				
IP	IP67 / 3.2 ft 30 minutes				
Heat resistance	300 °F for 15min / 500 °F for 5min				
	Sensor				
Micro bolometer type	Uncooled 17µ Amorphous Silicon aSi Resolution 384 x 288 (110 592 px)				
Spectral range	7 – 14 μm				
Thermal sensitivity	NETD: <50mK (<0.05℃)				
	Optic				
Material	Germanium Carbon Coated Protected by a germanium window				
Focus	1.15ft to infinity / F/1.3 speed				
Visual field / FOV	H: 51°/V: 40°/ Diagonal: 65°				

General				
Rechargeable batteries	LiFePO ₄ (Lithium Iron Phosphate = safety VS fire), 2.5Ah at 6.6V, 0.19lbs			
Running time (68 °F) with Eco-Boost- System since October 2018	Without video/photo functions: >8h (2 batt) / >4h (1 batt) With video/photo functions: >6h (2 batt) with non-active video >5h (2 batt) with recording video			
Boot time	< 5 seconds			
Charging voltage	12 / 24 VDC or 100-240 VAC			
Charging time (for 2 batt / half for 1 batt)	Charging bay: ~1h30 Mains charger: 100% in ~2h, 90% in ~1h30, 80% in ~1h20			
Charging cycles	> 5000			
Memory (optional)	8GB internal SD card (8h video or 1000 pics)			
Warranty	5 years on camera / 6 years on batteries / 10 years on thermal sensor / 1 year on accessories (chargers, charging bay, etc)			
	Options			
Removable pistol grip	Picture capture and/or video recording (8GB capacity)			
Neck strap in flame retardant material	Vehicle charging bay or mains charger			
1 or 2 Retractable lanyards	Carrying case IP67			
Protection hood	Wireless video transmission to computer, tablet or smartphone			
Analogue output (NTSC or PAL)				



Energy concept

LiFePO4 batteries (lithium-iron-phosphate). **Benefits:**

- -Very long lifespan guaranteed 5000 charging cycles (~10 years)
- -Operating time (8h with 2 batteries at the same time in the camera

Picture capture & Video recording

Pictures (up to 1000) and Video (up to 8h) can be:

- viewed on the camera screen during operation
- Live Pictures can be sent to a computer, tablet or smartphone thanks to optional wireless stick.

Wlan module

- Downloaded into a computer via a USB cable



Color Scheme

High-Gain Mode Freeze/ _ Picture

pointer

Video

Wlan Stick



Battery Indicator

1082°C

Hot Spot Temperature

Temper-

Very space-saving mountable! Power supply 12/24 VDC or 100-240 VAC. Can charge up to 4 batteries at the same time (2 in the camera and 2 spares)

1.800.561.8187

information@itm.com

Camera standard features:

	Color modes			Features							
Description	Color modes	Optional color modes	Max color modes	Battery	Freeze mode	Side trap	Video recording	Picture capture	Laser	Zoom	USB cable
TEMPEST TIC 4.3	Fire & Multicolour or Cold		5	2	V	2				V	
TEMPEST TIC 4.3 L		5	2	$\sqrt{}$	2			V	V		
TEMPEST TIC 4.3 V		5	2	V	2	V	V		V	$\sqrt{}$	
TEMPEST TIC 4.3 VL		5	2	V	2	V	V	V	V	V	

V= Video + Picture

L = Laser

Camera optional accessories:

	Wireless Transmission kit	Only compatible with cameras equipped with Video recording
III III	Pack of 2 spare batteries	
U	Cable charger for TIC 3 & 4	Available in 12/24V or 100V-240V
eres	Watertight Carrying case	IP67
T	Vehicle charging bay	Charge batteries inside the camera
*	Laser pointer	Only for 3.3 and 4.3 models

	Vehicle charging bay with additional slots	Charge batteries in the camera + 2 extra spare batteries		
	Power supply for charging bay	Exist in 12/24V and 100V-240V with US or EU plug		
	Retractable lanyard	1.1lbs or 2.2lbs tension force		
(9)	Neck strap	Fire-proof (Kevlar)		
	Protection hood	Increases exposure time x2 to high temperatures		
1	Removable pistol grip	Pistol grip = 0.37lbs Incl. mounting tool		





