

# PosiTest<sup>®</sup> **AT** Series Pull-Off Adhesion Testers

Measures the adhesion of coatings to metal,  
wood, concrete and other rigid substrates

Models available for conforming to **ASTM C1583** (tensile strength  
of concrete overlays) and **BS EN 12004** (cementitious adhesives).



*Available in Automatic  
or Manual models*



**DeFelsko**<sup>®</sup>  
The Measure of Quality



Available on the  
App Store



WiFi

1.800.561.8187

www.**itm**.com

information@itm.com

## Select from four Stand-offs...

### 20 mm Kit

- Ideal for measuring higher bond strength coatings on metals
- Can be used with optional 10 and 14 mm dollies
- Includes 20 mm aluminum dollies (20), 20 mm cutting tool and 20 mm stand-off



### 50 x 50 mm Tile Kit

- **NEW** Ideal for measuring the tensile strength of ceramic tile cementitious, dispersion and reaction resin adhesives
- Conforms to BS EN 12004-2
- Includes 50 mm x 50 mm steel dollies (4), and 50 mm x 50 mm stand-off



**PosiTest AT 50T KIT** converts the adhesion tester to measure the tensile strength of ceramic tile adhesives.

### 50 mm Kit

- Ideal for measuring lower bond strength coatings on wood, concrete and plastic
- Includes 50 mm aluminum dollies (8), 50 mm cutting tool and 50 mm stand-off

### 50 mm C1583 Kit

- **NEW** Ideal for measuring the tensile strength of concrete surfaces and concrete repairs and overlay materials
  - Conforms to ASTM C1583 and EN 1542
  - Includes 50 mm C1583 steel dollies (4), 50 mm diamond grit cutting tool with arbor and 50 mm C1583 stand-off
- NOTE: Drill required (not included)



**PosiTest AT-M with 50 mm C1583 Kit** measures the tensile strength of concrete surfaces, concrete repairs and overlay materials

## All Models Feature...



## Select from four Stand-offs...

### 20 mm Kit

- Ideal for measuring higher bond strength coatings on metals
- Can be used with optional 10 and 14 mm dollies
- Includes 20 mm aluminum dollies (20), 20 mm cutting tool and 20 mm stand-off



### 50 x 50 mm Tile Kit

- **NEW** Ideal for measuring the tensile strength of ceramic tile cementitious, dispersion and reaction resin adhesives
- Conforms to BS EN 12004-2
- Includes 50 mm x 50 mm steel dollies (4), and 50 mm x 50 mm stand-off



**PosiTest AT 50T KIT** converts the adhesion tester to measure the tensile strength of ceramic tile adhesives.

### 50 mm Kit

- Ideal for measuring lower bond strength coatings on wood, concrete and plastic
- Includes 50 mm aluminum dollies (8<sup>1</sup>), 50 mm cutting tool and 50 mm stand-off

### 50 mm C1583 Kit

- **NEW** Ideal for measuring the tensile strength of concrete surfaces and concrete repairs and overlay materials
  - Conforms to ASTM C1583 and EN 1542
  - Includes 50 mm C1583 steel dollies (4), 50 mm diamond grit cutting tool with arbor and 50 mm C1583 stand-off
- NOTE: Drill required (not included)



**PosiTest AT-M with 50 mm C1583 Kit** measures the tensile strength of concrete surfaces, concrete repairs and overlay materials

## All Models Feature...



# PosiTest<sup>®</sup> **AT** Series Pull-Off Adhesion Testers

Measures the adhesion of coatings to metal,  
wood, concrete and other rigid substrates

Models available for conforming to **ASTM C1583** (tensile strength  
of concrete overlays) and **BS EN 12004** (cementitious adhesives).



*Available in Automatic  
or Manual models*



**DeFelsko**<sup>®</sup>  
The Measure of Quality



Available on the  
App Store



WiFi

1.800.561.8187

www.**itm**.com

information@itm.com