

Features

- Detects all CFCs, HFCs, and HCFCs
- Quick response and high accuracy detects small leaks
- 15" (390mm) gooseneck for hard to reach areas
- Designed for one-handed operation
- User adjustable sensitivity (High/Low)
- Tricolor visual indicator
- Audible (buzzer) and visual (LED) alarm indicators
- Low battery indicator and auto shut off
- User replaceable sensor
- Includes reference leak source, batteries and hard carrying case

Specifications

Detected Gases: CFC's: R11, R12, R13
 HCFC's: R22, R502, R500
 HFC's: R134a, R123, R125, R23, R404A, R407C, R410A and other halogen based compounds
 HFO's: HFO-1234yf and R514A

Sensitivity: R22, 134A: 6g/year(H), 30g/year(L)
 R404A, 407C, 410A: 8g/year(H), 40g/year(L)

General Specifications

Sensor Type: Advanced ionization detector
 Display: Tricolor LED bar indicator
 Alarm: Audible (buzzer) and Visual (bar indicator)
 Sensitivity Settings: Low and High
 Warm-up Time: 10 seconds
 Response Time: Less than 1 second
 Auto Shut-off: Yes (after 10 mins)
 Low Battery Indicator: Yes
 Power Supply: 4 AA Batteries
 Battery Life: Approx. 40 hours
 Product Certifications: CE, RoHS
 Probe Length: 15" (390mm)
 Operating Temp.: 32 to 104°F (0 to 40°C)
 Storage Temp.: 14 to 140°F (-10 to 60°C)
 Operating Humidity: 10-70%
 Dimensions: 8.5 x 2.6 x 2.2" (217 x 66 x 56mm)
 Weight: 9.3 oz (265g)

TECHNICAL DATA



Model	Description
C-380	Refrigerant Leak Detector
R-134A	Replacement Sensor
LC-R01	Replacement Reference Leak Source
R8888	Hard Carrying Case
C-380-NIST	Refrigerant Leak Detector & NIST