



## Item # DQSA-F-4N-S, DQ Series Quick Connectors

### Features

- Simple to operate: Push to connect, pull body sleeve to disconnect.
- SS316 construction with standard FKM O-ring.
- Brass construction with standard NBR O-ring.
- No tools required to connect and disconnect.
- Compact and light weight.

### Operation

- Coupling: Align stem with body. Push stem into body until it clicks.
- Discoupling: Pull body sleeve toward stem.
- Coupling with an identical Series: i.e., Any DQSA Series stem fits any DQBA Series body.
- Non-valve stem: DQSA, DQSB and DQSC Series will remain open while disconnected.
- Do not connect or disconnect at pressures exceeding 250 psig (17.2 bar).

[Specifications](#) · [Dimensions](#)

### Specifications

Connector Part	Stem
Series	DQ A
Max Flow Rate Water at 20°C (68°F)	4.0 U.S. gal/min. (15 L/min.)
Stem Type	Non valve
Stem End Connection	Female NPT
Stem Size	1/4" Female NPT
Body Material	Stainless Steel 316
O-Ring	FKM
Stem Protector	Without Protector
Key Color	Standard (No Color)

### Dimensions

Cv (DQS)	0.3
Stem Overall Length (Non Valve)	57.4 mm