# **SHIMPO**INSTRUMENTS

Series DT-200LR Combination Contact/Non-Contact Laser Tachometers Laser-enabled precise RPM measurement up to 20 feet. The Series DT-200LR digital tachometers incorporate laser technology yet retain our hallmark rugged construction and reliable quality components. Units offer incredible value and versatility as they can operate in non-contact and contact applications. These instruments feature a field-upgradeable contact adapter for linear rate measure, conveniently allowing both non-contact and contact measurements. Incorporating the precise laser technology and user-friendly functions as the DT-200LR tachometer, the DT-200LR-S12 provides an exceptional accuracy in measuring speed and length via its 12" wheel. The larger wheel rotates more slowly than a standard 6" wheel, enabling reliable and safe registration of high speeds.

All Series 200LR units come standard with a NIST traceable calibration certificate. We're confident you'll agree that these fine units are the most advanced handheld tachometers on the market!

# Measuring Quality

## DT-200LR Combination Laser Tachometers



#### **Features**

- Outstanding Accuracy allows usage in the strictest applications
- Sophisticated laser beam detection to 20 feet provides operator safety during testing
- Exceptionally rugged die-cast aluminum housing enables usage in the harshest conditions
- Wide field selection of units in both instantaneous rate as well as totalized length satisfies a multitude of user requirements
- · Large 5 digit display aids user visibility
- 10 measurement memory capacity allows quick retrieval of stored data plus additional last, max. & min. values
- Long-life battery (25-40 hrs. continuous use) eliminates concerns of being down during testing
- Compact, Ergonomic design allows easy ergonomic grip
- Rear Threaded Inserts provides option to mount to stand or other device
- Available display options of either LCD or vibrant, bright red LED
- CE Mark combined with free NIST certificate provides a guarantee of quality performance







DT-207LR-S12 Contact Tachometer with Optional 12" Circle Wheel



Standard DT-200LR in Supplied Case



#### **DT-200LR Specifications**

| Display Range         | 6 - 99,999 rpm   |
|-----------------------|--|
| Accuracy              | ±1 rpm: 6 -8,300 rpm; ±2 rpm: 8,300 - 25,000 rpm; ±0.006% of reading ±1 digit (±6 rpm max.) 25,000 - 99,999 rpm  |
| Display               | DT-205LR: 5 digit 0.47" (12 mm) high<br>LCD; DT-207LR: 5 digit 0.4" (10 mm)<br>high LED  |
| Measuring Units       | rpm (on contact using adapter, in-<br>cluded) for YPM, mPM, FPM, IPM, and<br>Length: YRD, m, FT and IN   |
|                       | Use wheel with 200L adapter  |
| Measuring Distance    | 1" (25.4mm) to 20' (6m)  |
| Memory System         | 13 readings are stored in memory and retained for 5 minutes (last, max., min., and 10 extra measurements)  |
| Detection             | Laser diode / contact  |
| Update Time           | 1 second (typical)   |
| Power Requirement     | 2 AA 1.5V batteries<br>(Life: Approx. 25 hrs)  |
| Operating Temperature | 32° - 113°F (0° - 45°C)  |
| Construction          | Die-cast aluminum housing  |
| Product Weight        | 0.8 lb (365 g)   |
| Package Weight        | Approx. 2 lb (.91 kg)  |
| Approvals             | CE   |
| Dimensions            | 6.6" L x 2.4" W x 1.8"H<br>(167.5 mm x 60 mm x 46 mm)  |
|                       | with contact adapter:<br>Length=8.25" (209 mm)   |
| Warranty              | 1-Year   |
| Included Accessories  | Two AA Batteries, Reflective tape, 2 cone adapters, funnel adapter, 3½" extension shaft, carrying case, NIST certificate, master wheel (6" cir.) & contact adapter |
| Options               | -S12 Option: Same as DT-200LR except 6" dia. wheel replaced with 12" dia. contact wheel  |

#### **Ordering Details**

| DT-205LR     | Combination LCD Tachometer with laser sensor and contact adapter for use with included 6" contact wheel. Includes NIST certificate.  |
|--------------|--|
| DT-205LR-S12 | Combination LCD Tachometer with laser sensor and contact adapter for use with included 12" contact wheel. Includes NIST certificate. |
| DT-207LR     | Combination LED Tachometer with laser sensor and contact adapter for use with included 6" contact wheel. Includes NIST certificate.  |
| DT-207LR-S12 | Combination LED Tachometer with laser sensor and contact adapter for use with included 12" contact wheel. Includes NIST certificate. |

#### **Accessories**

| CONE         | 1/2 inch cone adapter                                |
|--------------|--|
| CONE-3/4     | 3/4 inch cone adapter                                |
| CONE-1-1/4   | 1-1/4 inch cone adapter                              |
| DT-ADP-200LR | Contact adapter for DT-200LR                         |
| DT-CARRY100  | Carrying case for handheld tachometers               |
| EXT-SHAFT    | 3.5 inch extension shaft for handheld tachometers    |
| FPM-12       | 12 inch circumference measuring wheel                |
| FPM-6        | 6 inch circumference measuring wheel                 |
| FPM-6-GV     | 6 inch circumference grooved measuring wheel         |
| FUNNEL       | 1/2 inch funnel adapter                              |
| FUNNEL-3/4   | 3/4 inch funnel adapter                              |
| ТАВ          | Sheet of thirty five 1/2 inch square reflective tabs |
| TAPE         | 1" x 7.75" strip of reflective tape                  |
| NIST-TACH    | NIST traceable certificate with data                 |

### **Included Accessories**



DISTRIBUTED BY:

#### **Optional Accessories**





