HI 98121















Specifications

		HI 98121			
Range	ORP	$\pm~1000~\text{mV}$			
	pН	-2.00 to 16.00 pH			
Temperature		-5.0 to 60.0°C / 23.0 to 140.0°F			
Resolution	ORP	1 mV			
	рН	0.01 pH			
Temperature		0.1°C/0.1°F			
Accuracy (@20	°C) ORP	± 2 mV			
	pН	±0.05 pH			
Temperature		$\pm 0.5^{\circ}$ C/ $\pm 1^{\circ}$ F			
Calibration	ORP	factory calibrated			
	рН	automatic, 1 or 2 points with 2 sets of memorized buffers			
		(pH 4.01 / 7.01 / 10.01 or 4.01 / 6.86 / 9.18)			
Temperature Compensation		automatic for pH readings			
Electrodes		HI 73127 replaceable pH electrode (included); fix ORP sensor			
Battery Type / Life		4 x 1.5V with BEPS / approx. 250 hours of continuous use;			
		auto-off after 8 minutes of non-use			
Environment		-5 to 50°C (23 to 122°F); RH max 100%			
Dimensions		163 x 40 x 26 mm (6.4 x 1.6 x 1.0")			
Weight		100 g (3.5 oz.)			

Accessories

HI 73127	Spare pH electrode	HI 70006P	pH 6.86 buffer solution, 20 mL
HI 73128 HI 7020M	Electrode removal tool 200/275 mV test solution,	HI 70007P	sachet, 25 pcs. pH 7.01 buffer solution, 20 mL
HI 7091M	230 mL bottle Reducing solution, 230 mL	HI 70009P	sachet, 25 pcs. pH 9.18 buffer solution, 20 mL
HI 7092M	bottle Oxidizing solution, 230 mL	HI 70010P	sachet, 25 pcs. pH 10.01 buffer solution, 20
HI 70004P	bottle pH 4.01 buffer solution, 20 mL	HI 70300M	mL sachet, 25 pcs. Electrode storage solution,
	sachet, 25 pcs.		230 mL bottle

For a complete range of calibration, cleaning and maintenance solutions, see section F.

Combination pH and ORP Tester

The Combo series of combination waterproof testers with advanced functions now includes the new model HI 98121 for simultaneous pH and ORP measurements.

HI 98121 also reads temperature, which is continuously displayed on the dual level LCD.

The pH electrode fiber junction can be easily pulled out for replenishment. The pH electrode cartridge can be quickly replaced with the supplied electrode removal tool. The encapsulated external stainless steel temperature sensor provides a fast response due to its close proximity to the pH electrode.

HI 98121 works with common batteries and when turned on, displays the percentage of remaining battery life. The stability indicator ensures reliable readings.

The body is ergonomically designed and the meter will float if dropped into

Ordering Information

HI 98121 is supplied complete with protective cap, electrode removal tool, batteries and instructions.

