IFC200 USB DATA LOGGER INTERFACE

MADGETECH WE BUILD DATA LOGGERS

Features

- Compatible With Most MadgeTech
 Data Loggers
- "Plug and Play" No Driver Installation Required
- Blue, Green and Red LED Indicators
 Beduced paics with langer concert
- Reduced noise with longer sensor leads

MadgeTech's IFC200 interface cable communicates between stand alone data loggers and the MadgeTech software. Through this interface, loggers can be started, stopped or downloaded.

The IFC200 has been redesigned, and is



now "plug and play". It can be directly connected to a computer without installing any drivers. The improved IFC200 can now operate at up to 500 Volts RMS relative to the computer's earth ground when attached.

The IFC200 is equipped with communication LE device status. The blue light illuminates when the device is plugged in and successfully recognized by Windows. The red light flashes when data is sent, and the green light flashes when data is received.



IFC200 SPECIFICATIONS*

Operating Environment:	-20°C to +50°C (-4°F to +122°F)	LEDS:	Blue and Red/Green
Materials:	Polycarbonate Enclosure		Blue: Illuminates when the device is plugged in and successfully recognised by Windows.
Dimensions:	Enclosure: 1.9" x 0.69" x 0.32 (48.4mm x 17.5mm x 8.1mm)	LED Functions:	, , ,
	Cable: 6' included May be used with any shielded 3.5mm stereo cable up to 100'		Green: Flashes when data is received.

ORDERING INFORMATION

MODEL		DESCRIPTION	ASK AB	Tempera Humid Pressu	ity
IF	C200	USB Data Logger Interface	OUR OT DAT LOGG	HER pH	pH Level
			LOGGI	LCD Dis	
				Pulse/Even	
				Currer	
				Voltag	e
				Wirele	SS
				Intrinsical	y Saf
				Spectral Vil	oratio
				Motio	n

REV 5 03.10.2017

information@itm.com

1.800.561.8187

