



J-2000 moisture meter



For many purposes, the J-2000 helps to keep up with ever-changing job conditions. With built-in wood species correction and temperature correction, along with storage and informative reading statistics the J-2000 is an extremely versatile tool at a great value.



Your Benefits:

- Bright, clear digital display
- Corrects for 48 individual wood species and temperature (°F and °C)
- Averages up to 100 accumulated readings
- Moisture Range: 6%-40% on wood, also available with 6%-60% moisture range
- Built-in calibration check
- Integral contact pins mounted on top of meter provide 8mm (5/16") penetration
- Built-in connector accepts any Delmhorst electrode
- Size: 20x8x4cm (8x3x1 5/8")
- Weight: 285gr. (10 oz.)
- Rugged construction ensures years of reliable use
- Sturdy plastic carrying case
- 9V battery
- 1-year warranty

Special Packages:

Moisture meter package **J-2000/PKG:**

Includes meter with MC 6%-40%, 26-ES electrode, extra contact pins for the meter, extra 496 pins for 26-ES hammer electrode

Moisture meter package **J-2000/6-60/PKG:**

Includes meter with MC 6%-60%, 26-ES electrode, extra contact pins for the meter, extra 496 pins for 26-ES hammer electrode

Moisture meter package **J-2000/SC/PKG:**

Includes meter, Scandinavian version with MC 6%-40%, 26-ES electrode, extra contact pins for the meter, extra 496 pins for 26-ES hammer electrode



MCS-1 - Moisture content standards are great for verifying that your Delmhorst moisture meter is in calibration. The MCS-1 can be used on any meter with a wood scale. With two electrical resistance values (12% and 22%) to test your meter against, you can be sure that your readings will stand up to the strictest standards of accuracy.

J-2000 moisture meter



Available electrodes:



26-ES Hammer electrode

Easily check high density hardwood that short pins are unable to penetrate.

It will also easily penetrate through flooring to plywood sub-floor or concrete.



2-E pin electrode

Great for hard to read areas.

Use on timber, poles and veneer.



830-X Wood

Pen electrode available in different lengths:

830-2 – 25cm (10")

830-3 – 45cm (18")

830-4 – 90cm (36")

(Requires H-4 Handle)

For moisture measuring in sawdust



H-4

Handle for electrodes 830-x, 831 and 832.

Two handed operation is recommended over using an electrode that connects directly to the top of the meter (like our 1235 series) to minimize stress placed on the meter casing.



19-E Wood

Blade type electrode.

Available blade lengths:

125mm (5")

300mm (12")

450mm (18")

Electrode designed for measuring in wood pellets, shavings, tree bark, etc.



15-E Wood

Pin type, with two rows of four pins each, maximum penetration 3mm (1/8"). Penetration can be adjusted according to stock thickness by means of gauge block.

Used for veneer.



22-E

Pin type, comes with A-111 uninsulated contact pins for 38mm (1 1/2") penetration. Will also accept 496, insulated pins, 29mm (1 1/8") penetration

For use on plaster, masonry and wood



4-E

Pin type, comes with 4 uninsulated 2497/A-100 contact pins for 8mm (5/16") penetration

Use on kiln-dried boards up to 5cm (2") and on air-dried boards up to 32mm (5/4")