

Multi Gas Clip

The first portable multi gas detector
with a battery life of months instead of hours.



- ▶ 2-month battery life on a single charge
- ▶ Compact and lightweight
- ▶ 6-month calibration cycle
- ▶ Low maintenance cost
- ▶ Simple to use
- ▶ 100% quality control testing
- ▶ LEL sensor (IR) does not require oxygen




IR Reader



MGC-DOCK

Specifications

Size	4.7 x 2.4 x 1.2 in. (118.6 x 61.6 x 31.7 mm.)
Weight	7.7 oz. (240 g)
Temperature	-4 to +122°F (-20 to +50°C)
Humidity	5% to 95% RH (non-condensing)
Battery Life	IR 75 days continuous Pellistor 26 hours (typical)
Alarms	Visual, Vibrating, Audible (minimum 95dB) Low, High, STEL, TWA and OL (Over Limit)
LEDs	4 red alarm bar LEDs Yellow backlight (activated on button press) Red backlight (activated on alarm condition) Yellow Maintenance Notification LED
Tests	Full function self-test upon activation Sensors, battery and circuitry continuous
Ingress Protection	IP66/67 (Resistant to water jets and submersion up to 1m)
Certifications and Approvals	 CAN/CSA C22.2 No. 157 and C22.2 152 ANS/UL-913 and ANSI/ISA – S12.13 Part 1 CSA: Class 1, Division 1, Group A, B, C, and D IECEX: Ex ia IIC T4 Ga ATEX: Pending

Warranty	Full 2 years																
Gasses	<table border="0"> <tr> <td>H₂S</td> <td>0 – 100 PPM</td> </tr> <tr> <td>CO</td> <td>0 – 500 PPM</td> </tr> <tr> <td>Combustible</td> <td>0 – 100 %LEL</td> </tr> <tr> <td>O₂</td> <td>0 – 30 %</td> </tr> </table>	H ₂ S	0 – 100 PPM	CO	0 – 500 PPM	Combustible	0 – 100 %LEL	O ₂	0 – 30 %								
H ₂ S	0 – 100 PPM																
CO	0 – 500 PPM																
Combustible	0 – 100 %LEL																
O ₂	0 – 30 %																
Sensor Type	H ₂ S, CO, O ₂ : Plug-in electrochemical cell Combustible: Plug-in Infrared (IR) or catalytic bead																
User Options	<table border="0"> <tr> <td>User Message</td> <td>Maintenance Notification</td> </tr> <tr> <td>TWA/STEL Intervals</td> <td>TWA Method</td> </tr> <tr> <td>Language (6)</td> <td>Sensor Disable</td> </tr> <tr> <td>Latching Alarms</td> <td>SAFE Display</td> </tr> <tr> <td>Self-Test Lock</td> <td>Dock Lock</td> </tr> <tr> <td>Auto-zero on start up</td> <td>Calibration gas</td> </tr> <tr> <td>Bump Test Interval</td> <td>Calibration Interval</td> </tr> <tr> <td>Low/High Alarm</td> <td>TWA/STEL Alarm</td> </tr> </table>	User Message	Maintenance Notification	TWA/STEL Intervals	TWA Method	Language (6)	Sensor Disable	Latching Alarms	SAFE Display	Self-Test Lock	Dock Lock	Auto-zero on start up	Calibration gas	Bump Test Interval	Calibration Interval	Low/High Alarm	TWA/STEL Alarm
User Message	Maintenance Notification																
TWA/STEL Intervals	TWA Method																
Language (6)	Sensor Disable																
Latching Alarms	SAFE Display																
Self-Test Lock	Dock Lock																
Auto-zero on start up	Calibration gas																
Bump Test Interval	Calibration Interval																
Low/High Alarm	TWA/STEL Alarm																

Part #	Description
MGC	4 Gas Monitor with infrared sensor
MGC-P	4 Gas Monitor with pellistor sensor
MGC-DOCK	4 bay calibration and bump test station
GCT-IR-LINK	GCT IR communication module w/ USB cable
MGC-CS-KIT	MGC Confined Space Kit (monitor and gas sold separately)
Please contact Gas Clip Technologies for additional spares, accessories and gas.	