

Pressure Module (PM)

ACCURACY

psi (Gauge Pressure)	psiA (Pressure with BARO module)
30, 100, and 300 psi modules	30 psi module
0 to 30% of Range: \pm (0.0075% of Full Scale)	0.200 to 14.500 psiA: \pm 0.011 psiA
30 to 110% of Range: \pm (0.025% of Reading)	14.500 to 44.500 psiA: \pm (0.025% of Reading) + 0.003 psiA
Vacuum: For 30 and 100 psi \pm (0.06% of Full Scale*)	100 psi module
For 300 psi \pm (0.06% of Full Scale*) \pm 1 LSD	0.200 to 14.500 psiA: \pm 0.011 psiA
* Full Scale = -14.5 psi	14.500 to 44.500 psiA: \pm 0.011 psiA
1000, 3000, 10 000, and 15 000 psi modules	44.500 to 114.500 psiA: \pm (0.025% of Reading)
0 to 30% of Range: \pm (0.015% of Full Scale)	300 psi module
30 to 110% of Range: \pm (0.05% of Reading)	0.20 to 14.50 psiA: \pm 0.01 psiA
	14.50 to 104.50 psiA: \pm 0.03 psiA
	104.50 to 314.50 psiA: \pm (0.025% of Reading)
	1000 psi module
	14.5 to 314.5 psiA: \pm 0.2 psiA
	314.5 to 1014.5 psiA: \pm (0.05% of Reading)
	3000 psi module
	14.5 to 914.5 psiA: \pm 0.5 psiA
	914.5 to 3014.5 psiA: \pm (0.05% of Reading)
	10 000 psi module
	15 to 3015 psiA: \pm 2 psiA
	3015 to 10 015 psiA: \pm (0.05% of Reading)
	15 000 psi module
	15 to 4515 psiA: \pm 3 psiA
	4515 to 15 015 psiA: \pm (0.05% of Reading)

Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.

All models indicate vacuum, but vacuum specification applies to 30, 100, and 300 psi models only.

Not recommended for continuous use at high vacuum. Refer to [XP2i-DP data sheet](#) for gauges that are intended for continuous high vacuum use.



4791.0.2001 • nVision psi

DIFFERENTIAL PRESSURE MEASUREMENT UNCERTAINTIES WITH TARE

The Tare function can improve measurement uncertainties on two modules with the same full scale pressure range installed into one nVision Reference Recorder. Requires the use of an equalizing valve.

The following specifications apply to the measurement system with a logging interval of 1 second/reading:


Full Scale Range of Both Sensors	The Greater of (+/-)				or	% of DP Reading
	psi	mbar	inH ₂ O	mmH ₂ O		
30	0.0005	0.04	0.014	0.4		0.025%
100	0.0015	0.10	0.04	1.0		0.025%
300	0.005	0.4	0.14	4.0		0.025%
1000	0.02	1.0	0.4	10.0		0.05%
3000	0.05	4.0	1.4	n/a		0.05%
10000	0.2	10.0	4.0	n/a		0.05%
15000	0.3	15.0	6.0	n/a		0.05%

Unit must be enabled in CrystalControl

DIFFERENTIAL PRESSURE MEASUREMENT UNCERTAINTIES WITHOUT TARE

The total nVision Reference Calibrator measurement uncertainty in the ΔP mode configuration will need to consider the uncertainties of both pressure modules. We recommend the module uncertainties to be combined with the preferred square root of the sum of the squares (or "root sum squares") method.

The following table lists the possible combinations of using Pressure Modules (PM) with different accuracy statements. The uncertainties reported below are without the use of the Tare feature, which will greatly improve your measurement uncertainty.

		 Upper Pressure Module Uncertainties (of Static Line Pressure) (of Reading)	
		0.025%	0.05%
Lower Pressure Module Uncertainties (of Static Line Pressure) (of Reading)	0.025%	0.035%	0.056%
	0.05%	0.056%	0.071%

4791.O.2001 - nVision psi

SENSOR

Wetted Materials: (WRENCH TIGHT) **316 stainless steel**
(FINGER TIGHT) **316 stainless steel**
and Viton® (internal o-ring)

Diaphragm Seal Fluid: **Silicone Oil**

Connection: **Crystal CPF ♦ Female**

All welded, with a permanently filled diaphragm seal.

Metal to metal cone seal; O-ring can be removed if necessary.

1/4" medium pressure tube system compatible with HIP LM4 and LF4 Series, Autoclave Engr SF250CX Male and Female Series.

CPF Adapters to NPT, BSP, and M20 available.

♦U.S. Patent No. 8,794,677

BAROMETRIC REFERENCE (BARO)

Accuracy: **± 0.00725 psi, ± 0.5 mbar**

Range: **10.153 to 15.954 psiA,**
700.0 to 1100.0 mbarA

Units and Resolution: **psi** **0.001**
inHg **0.001**
mmHg **0.01**
mbar **0.1**

Pressure Connection: **Cylindrical sensor fitting of 5.8mm**
OD. A flexible 4.8 mm [3/16"] ID
tube is recommended to connect for
for calibration.

Mounting: **Secured using a 3/8" 4-40 plastic screw.**

Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.

Exposure to environmental extremes of temperature, shock, and/or vibration may warrant a more frequent recertification period.

Other units available depending on the installed modules.



4791.0-2001 • nvision psi

Current, Voltage, & Switch Test Module (MA20)

Intended for use with a 4-20mA loop measurement. This module is also capable of measuring supply voltages and has an auxiliary fixed output for use in switch open/closure testing. Each MA20 module includes a super flexible silicone test lead kit (P/N 3952).

CURRENT & VOLTAGE MEASUREMENT

Current (mA) Input

Accuracy: $\pm (0.015\% \text{ of rdg} + 0.002 \text{ mA})$	<i>Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.</i>
Range: 0 to 55 mA (MA20)	
Max Allowable Current: 93.3 mA	For hazardous location product warnings, refer to the operation manual.
Resolution: 0.001 mA or 0.01%	<i>Inputs protected by a resettable fuse.</i>
Units: mA, % 4-20, % 10-50	<i>mA can be displayed as a percentage, where 0 to 100% corresponds to either 4 to 20 mA or 10 to 50 mA.</i>
Input Resistance: < 17.2 Ω	<i>Jacks are compatible with safety sheathed banana plugs.</i>
Voltage Burden @ 20mA: < 0.35 V	
Voltage Burden @ 50mA: < 0.86 V	
HART Resistance: 250 Ω	
Connection: 2mm jacks	



Voltage (VDC) Input

Accuracy: $\pm (0.015\% \text{ of rdg} + 0.002 \text{ VDC})$	<i>Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.</i>
Range: 0 to 28 VDC	
Max Allowable Voltage: 30 VDC	
Resolution: 0.001 VDC	
Units: VDC	

Switch Test

Switch Type: Dry Contact	AMETEK SENSORS, TEST & CALIBRATION
Closed State Resistance: < 10 Ω	<i>Switch state change indicated by bright green LED flash.</i>
Open State Resistance: > 10 MΩ	<i>Switch test screen reports switch open, close, and deadband values.</i>

ATEX and IECEx Scheme Entity Parameters

The MA20 Module has these specific input entity parameters:

Ui = 28 V	Uo = 6.6 V
Ii = 93.3 mA	Io = 4.45 mA
Pi = 653.3 mW	Po = 7.34 mW
CI = 0.36 uF	Co = 0.5 uF*
Li = 39.1 uH	Lo = 12 uH**

* Dependent on the supply to the terminals but shall not be greater than 0.5 uF

** Total cable inductance between all modules

4791.02001 • nVision psi

Temperature Module (RTD100)

Calibrated for Pt100 RTD / PRT (100 Ohms at 0°C Platinum Resistance Temperature Detector) sensors conforming to DIN/ IEC 60751 (or IEC751) with US, Euro, or Lab calibration curves. An RTD is not included, but each RTD100 includes P/N 3953 RTD Connection Kit.

TEMPERATURE MEASUREMENT

Resistance Input

Accuracy: $\pm (0.015\% \text{ of rdg} + 0.02 \Omega)$ *Includes all effects of linearity, hysteresis, repeatability, temperature, and stability for one year.*

Range: **0 – 400 Ohms range for use with 100 Ohm PRTs**

Resolution: **0.01 on all scales**

Units: **°C, K, °F, R, Ω**

TCRs: **0.003850 $\Omega/\Omega/^\circ\text{C}$ (IEC 60751), 0.003911 $\Omega/\Omega/^\circ\text{C}$ (US Industrial Std), 0.003926 $\Omega/\Omega/^\circ\text{C}$**

Wiring: **2-, 3-, 4-wire support**

Connection: **M8 connector cable or terminal block**

The proper selection of the RTD sensing element is very important as the error associated with this device is the majority of the overall system measurement uncertainty. IEC 751 is the standard that defines the temperature versus resistance for 100 Ω , 0.00385 $\Omega/\Omega/^\circ\text{C}$ platinum RTDs. IEC 751 defines two classes of RTDs: Class A and B. Class A RTDs operate over the -200 to 630°C range versus -200 to 800°C for the Class B elements. For example, the Class A uncertainty is about half that of the Class B elements as illustrated in the following table.

Temperature °C	nVision Uncertainty		Class A				Class B			
			Class A Uncertainty		nVision + Class A Uncertainty		Class B Uncertainty		nVision + Class B Uncertainty	
	$\pm \Omega$	$\pm ^\circ\text{C}$	$\pm \Omega$	$\pm ^\circ\text{C}$	$\pm \Omega$	$\pm ^\circ\text{C}$	$\pm \Omega$	$\pm ^\circ\text{C}$	$\pm \Omega$	$\pm ^\circ\text{C}$
-200	0.02	0.05	0.24	0.55	0.24	0.55	0.56	1.30	0.56	1.30
0	0.04	0.09	0.06	0.15	0.07	0.17	0.12	0.30	0.12	0.31
200	0.05	0.13	0.2	0.55	0.21	0.56	0.48	1.30	0.48	1.31
400	0.06	0.17	0.33	0.95	0.33	0.96	0.79	2.30	0.79	2.31
600	0.07	0.21	0.43	1.35	0.44	1.37	1.06	3.30	1.06	3.31
800	0.08	0.25	0.52	1.75	0.53	1.77	1.28	4.30	1.28	4.31

ATEX and IECEx Scheme Entity Parameters

The RTD100 Module has these specific input entity parameters:

Ui = 0 V **Uo = 9.73 V**
Ii = 0 A **Io = 1.6642 A**
Pi = 0 W **Po = 1.1 W**
Co = 0.5 uF
Lo = 12 uH*

* Total cable inductance between all modules

nVision Chassis (NV)

OPERATING TEMPERATURE

Temperature Range: **-20 to 50° C (-4 to 122° F)**

< 95% RH, non-condensing. No change in accuracy over operating temperature range. Gauge must be zeroed to achieve rated specification.

Applies to all modules.

DISPLAY

Screen: **255 x 160 pixel graphical display**

LCD readable in sunlight with bright backlight.

Display Rate: **4 readings/second (standard)
up to 10 readings/second (recording)**

POWER

The nVision is Intrinsically Safe only if powered by one of the following battery types.

ATEX/IECEX:	Approved Battery Type	Ta=	Marking
	Rayovac Max Plus 815	-20 to 50° C	Ex ia IIB T4 Ga
	Duracell MN1500	-20 to 45° C	
	Energizer E91, EN91	-20 to 50° C	Ex ia IIB T3 Ga
	Duracell MN1500		

CSA:	Approved Battery Type	Ta=	Marking
	Rayovac Max Plus 815	-20 to 50° C	Class I, Division 1, Grp C, D T4
	Duracell MN1500	-20 to 45° C	
	Energizer E91		Class I, Division 1, Grp C, D T3B
	Energizer EN91	-20 to 50° C	Class I, Division 1, Grp C, D T3A
	Duracell MN1500		Class I, Division 1, Grp C, D T3C

4 x AA: **200 hours, typical**

Ultra Low Power: **Up to 60 days, typical***

*2 installed modules, 1 reading per 5 minute recording interval, and 23°C ambient temperature.

Uses 4 alkaline AA (LR6) batteries. Use of backlight reduces operating time.

For hazardous location product warnings, refer to the operation manual.

DATA/COMMUNICATION

Digital Interface: **mini-USB**

The mini USB will power the nVision with or without the battery pack installed.

For hazardous location product warnings, refer to the operation manual.

DATALOGGING

Capacity: **Approx. 1,000,000 data points***

**Single Module Recording*

Storage Type: **Non-volatile flash memory**

Limit of 64 individual recordings.

Fastest Interval: **10 per second**

The included CrystalControl software is compatible with Vista (SP 2), Windows 7 (SP 1), Windows 8.1 and Windows 10.

Slowest Interval: **1 per hour**

Produces csv, xls, pdf, or signed pdf files, and uses Excel template files (samples included) to automatically format and graph data.

ENCLOSURE

Weight: **680 g (24.0 oz)**

Weight includes one pressure module, one RTD module, 4AA battery module, and protective boot.

Rating: **IP66 and IP67**



Submersible to 1 m for 30 minutes [IEC 60529].

Housing: **Impact resistant injection molded**

LCD protected from impact damage by 1.5 mm (0.06") thick polycarbonate lens.

Keypad and Labels: **UV Resistant Polyester**

Mounting: **M4 x 0.7 [8 mm (0.31")] deep threaded insert mounting locations**

Skydrol® compatible.

For hazardous location product warnings, refer to the operation manual.

STORAGE TEMPERATURE

Temperature Range: **-40 to 75° C (-40 to 167° F)** *Batteries should be removed if stored for more than one month.*

SPECIAL FEATURES

The following requires the use of our free **CrystalControl** software

- Averaging Screen: **Averages all points in a recording run.**
- Data Point Counter: **Screen for counting the data points logged.**
- Display Screens: **Turn on and rearrange display screens.**
- Estimated Recording Time: **A CrystalControl calculation based on active screens and logging interval.**
- Live PC Graph: **During a recording, graph directly to your PC.**
- Password Protect: **Changes to configuration or userspan calibration factor(s).**
- Pressure Switch Test: **Using a PM and MA20, get deadband and state-change pressure.**
- Remove: **Unwanted pressure units.**
- Run Tags: **Create and enable run tags that will identify logging runs.**
- Screen Numbers: **Number each display screen to make writing procedures around the nVision easier.**
- Secure Documents: **Download into secure pdf documents for tamper proof records.**
- Start-up Screen: **Define a 32-character prompt which requires user acknowledgement at startup.**
- User Defined Unit: **Define and display any pressure units not included, or to use the gauge to display force, level or other pressure related parameters.**

STANDARD DELIVERY


- nVision Recorder
- CD Manual
- ISO 17025 Accredited Calibration Certificate, NIST Traceable
- Soft Carrying Case **P/N 5535**
- Protective Boot **P/N 3985**
- Mini-USB Cable **P/N 3951**

COMPLEMENTARY PRODUCTS


Crystal Engineering offers a wide range of products that work with the nVision:


- **Fit the nVision to your system without tools, safely and without leaks**
- **Lightweight, super flexible high pressure hoses**
- **Fitting kits and adapters**
- **Pneumatic hand pumps**
- **Hydraulic hand pumps**
- **Portable pressure comparators**
- **Software, for the quickest way to calibrate pressure transmitters and gauges**


CERTIFICATIONS


 **II 1G Ex ia IIB T4 Ga or T3
SIRA 09 ATEX 2008X**

  **Ex ia IIB T4 Ga or T3
IECEX SIR 09.0053X**

 Exia Intrinsically Safe and Non-incendive for Hazardous Locations: Class I, Division 1, Groups C and D, Temperature Code T4 / T3A / TCB / T3C. For hazardous location product warnings, refer to the operation manual.

 nVision complies with the Electromagnetic Compatibility and the Pressure Equipment Directives.

 nVision complies with the Australian Radiocommunications (Electromagnetic Compatibility) Standard 2008.

 nVision is approved for use as a portable test instrument for Marine use and complies with Det Norske Veritas' Rules for Classification of Ships, High Speed & Light Craft and Offshore Standards.

ACCESSORIES

- BARO Calibration Kit P/N 4547**
- Magnetic Hanging Strap P/N 5177**
- Waterproof Carrying Case P/N 2888**
- RTD Terminal Block P/N 3953 (included with RTD100 module)**
- Test Lead Kit P/N 3952 (included with MA20 Module)**

RANGE & RESOLUTION TABLE

PM	Range (psi)	Over-pressure	Display Resolution									
			psi	in H ₂ O	in Hg	mm Hg	mm H ₂ O	kg/cm ²	bar	mbar	kPa	MPa
30PSI	30	3.0 x	0.001	0.01	0.001	0.01	1	0.0001	0.0001	0.1	0.01	
100PSI	100	2.0 x	0.001	0.1	0.01	0.1	1	0.0001	0.0001	0.1	0.01	0.00001
300PSI	300	2.0 x	0.01	0.1	0.01	0.1		0.001	0.001	1	0.1	0.0001
1KPSI	1000	2.0 x	0.1		0.1			0.001	0.001		0.1	0.0001
3KPSI	3000	1.5 x	0.1		0.1			0.01	0.01		1	0.001
10KPSI	10 000	1.5 x	1					0.01	0.01		1	0.001
15KPSI	15 000	1.3 x	1					0.01	0.01		1	0.001

(Add one digit of resolution for differential mode.)

ORDERING INFORMATION

4791.O 2001 - nVision psi

Model	Power	Upper Module	Lower Module	BARO Module	Pump System*	Carrying Case™
NV	4AA					
	Pressure:	PM	PM	No ... (omit)	No Pump.... (omit)	
	Current, Voltage, and Switch:	MA20	MA20	Yes... -BARO	System A.... -AXX	Aluminum ... (omit)
	Temperature:	RTD100	RTD100		System A.... -AHX	Waterproof..... -W
	Blank Plate:	BNKPLT	BNKPLT		System B.... -BXX	
					System B.... -BHX	
					System C.... -CXX	
					System C.... -CHX	
					System D.... -DOX	
					System D.... -DWX	
					System E.... -EOX	
					System F.... -FOV	
					System F.... -FVW	
					System G.... -GOX	
					System G.... -GWX	
					System H.... -HOX	

If ordering an nVision with only one module installed, enter **BNKPLT** in the empty module slot.

SAMPLE PART NUMBERS

NV-4AA-30PSI-3KPSI-BARO nVision with 30 psi pressure module (upper) and 3000 psi pressure module (lower) and a BARO module option.

NV-4AA-RTD100-10KPSI-GWX-W nVision with RTD100 temperature module (upper) and 10 000 psi pressure module (lower); a System G pump system; and a waterproof carrying case.



AMETEK offers a variety of solutions for pressure generation and measurement. Our line of products for pressure generation includes everything from small pneumatic hand pumps to a precision, hydraulic pressure comparator capable of generating up to 15 000 psi / 1000 bar / 100 MPa.

All of our pumps may be ordered as part of a Pump System, complete with an nVision and delivered in a sturdy carrying case with custom insert.

* Refer to the following page for a more detailed description of each pump system.

Ordering a Pump System Only

Any pump system, carrying case, and connection fittings for an nVision reference recorder may be ordered separately from the gauge. Enter NV-NONE followed by the Pump System part number and the Carrying Case option code.

SAMPLE PART NUMBERS

NV-NONE-GWX-W System G pump system with a waterproof carrying case.

PUMP SYSTEMS OVERVIEW

Pump System	Part Number	Pressure Range	Pneumatic	Hydraulic	Hand Pump	Bench Top	Included Pump	Case Options	
								Aluminum	Waterproof (Pelican Case)
System A	AXX	0 to 30psi /2 bar	■		■		T-960-CPF	■	■
	AHX	0 to 580 psi /40 bar	■		■		T-970-CPF	■	■
System B	BXX	-25 inHg to 30 psi /-0.85 to 2 bar	■		■		T-965-CPF	■	■
	BHX	-27 inHg to 580 psi /-0.91 to 40 bar	■		■		T-975-CPF	■	■
System C	CXX	0 to 3000 psi /200 bar		■ (Oil)	■		T-620-CPF	■	■
	CHX	0 to 5000 psi /350 bar		■ (Oil)	■		T-620H-CPF	■	■
System D	DOX	0 to 5000 psi /350 bar		■ (Oil)		■	P-018-CPF	■	
	DWX	0 to 5000 psi /350 bar		■ (Water)		■		■	
System E	EOX	0 to 10 000 psi /700 bar		■ (Oil)		■	P014-CPF	■	
System F	FOV	0 to 15 000 psi /1000 bar		■ (Oil)		■	T-1-CPF	■	
	FWV	0 to 15 000 psi /1000 bar		■ (Water)		■		■	
System G	GOX	0 to 15 000 psi /1000 bar		■ (Oil)		■	GaugeCalHP		■
	GWX	0 to 15 000 psi /1000 bar		■ (Water)		■			■
System H	HOX	-27 inHg to 580 psi /-0.91 to 40 bar	■		■		T-975-CPF (and)		■
		0 to 5000 psi /350 bar		■ (Oil)	■		T-620H-CPF		■