

Features

- Measures ambient temperature and relative humidity
- Designed for one-handed operation
- Backlit dual LCD display
- User selectable °F/°C
- Max, min and data hold functions
- Low battery indicator and auto shut off
- Includes batteries

TECHNICAL DATA

Specifications

Temperature

Measuring Range: 14 to 140°F (-10 to 60°C)
 Accuracy: ±2.0°F (1.0°C)
 Resolution: 0.1°F/°C

Humidity

Measuring Range: 0 to 100% RH
 Accuracy: ±5% RH
 Resolution: 0.1% RH

General Specifications

Display: Dual LCD
 Backlit Display: Yes
 Data Hold: Yes
 Max: Yes
 Min: Yes
 Sampling Rate: 1 time/second
 Overrange Indicator: Yes
 Auto Shut-off: Yes (after 5 minutes, off)
 Low Battery Indicator: Yes
 Power Supply: 3 "AAA" Batteries
 Product Certifications: CE
 Operating Temperature: 32 to 122°F (0 to 50°C)
 Storage Temperature: 14 to 140°F (-10 to 60°C)
 Operating Humidity Range: 10 to 80%
 Dimensions: 6.3 x 2 x 1.1"
 (155 x 50 x 28mm)
 Weight: 4.2oz (102g)



Model	Description
R1910	Temperature & Humidity Meter, Compact Series
CA-52A	Soft Carrying Case