

### TECHNICAL DATA



### Features

- Compact design allows for one-handed operation
- Multi-angle measurement (20° / 60° / 85°)
- Backlit LCD display
- Auto calibration
- Internal memory stores last 254 data points
- Built-in rechargeable battery
- Designed to meet ASTM D523, ASTM D1455, ASTM C584 and ASTM D2457 international standards
- Includes ac adapter, calibration standard, cleaning cloth and hard carrying case

### Specifications

Measuring Range:	0.1 to 200 GU
Measuring Geometry:	20° / 60° / 85°
Accuracy:	±1.0 GU
Resolution:	0.1 GU
Repeatability:	±0.5 GU
Measuring Area:	7x14mm (Ellipse)
Display:	LCD
Backlit Display:	Yes
Auto Shut-off:	Yes (after 30 mins)
Low Battery Indicator:	Yes
Power Supply:	Rechargeable Lithium Battery
Internal Memory:	Yes (up to 254 datapoints)
Product Certifications:	CE / RoHS
Operating Temperature:	32 to 104°F (0 to 40°C)
Storage Temperature:	-4 to 140°F (-20 to 60°C)
Operating Humidity Range:	0 to 85%
Dimensions:	5.5 x 1.8 x 3" (140 x 45 x 75 mm)
Weight:	10.76oz (305g)

Model	Description
R7700	Gloss Meter
R8888	Hard Carrying Case