

Portable Radiation Dosimeter Model **R8008**



TECHNICAL DATA

Alpha, Beta, Gamma, X

0.0001 to 1000µSv/h

O to 4000cpm/cps

0.001µSv to 9999Sv

Alpha: From 4.0 MeV

Beta: From 0.2 MeV

Gamma: From 0.02 MeV X: From 0.02 MeV

<10% (less than 500μ Sv/h) <20%(less than 600μ Sv/h)

(Audible/Visual Indicators)

(up to 4000 groups of data)

Yes (Wireless via Bluetooth)

Windows XP / 7 / 8 / 10

32 to 122°F (O to 50°C)

14 to 140°F (-10 to 60°C)

Yes (after 10 mins/off)

2 to 120 seconds

O to $0.2\mu Sv/h$

4 AA Batteries

Yes (Included)

10 to 80%

7.9 x 2.8 x 1.9"

7.3oz (206g)

(200 x 70 x 45mm)

O to 9999

Dual LCD

Yes

Yes

Yes

Yes

Yes

Yes

Yes

CE





Features

- Detects Alpha, Beta, Gamma, and X radiation
- Automatic selection of measurement range
- Average time and pulse counting functions
- Large backlit LCD display with bargraph indicator
- Accumulation of radiation detection values and conversions between different measurement units
- User-adjustable alarms (audio/visual indicators)
- Internal memory stores up to 4000 groups of data internally
- Bluetooth connectivity wirelessly streams data to computer via software
- · Low battery indicator and auto shut off

1.800.561.8187

Includes batteries, software and hard carrying case

Specifications

Measured Rays: Radiation Dose Range: Pulse Dose Rate Range: Accumulated Radiation Dose Value: Accumulated Pulse Dose Rate: Sensitivity:

Accuracy:

Display: Backlit Display: Digital Bargraph Indicator: Adjustable Alarms:

Average Time Function: Natural Environment Reading: Datalogging Capabilities: Real-Time Clock and Date Stamp: Internal Memory:

Auto Shut-off: Low Battery Indicator: Power Supply: PC Connectivity: Software: Software OS Compatibility: Product Certifications: Operating Temperature: Storage Temperature: Operating Humidity: Dimensions:

Weight:

Model	Description
R8008	Portable Radiation Dosimeter
CA-05A	Soft Carrying Case



information@itm.com