Data Logging Sound Level Meter Model **R8080**



TECHNICAL DATA



Features

- High accuracy of ±1.4 dB meets Type 2 standards
- Triple range measurement (60dB dynamic range)
- A & C frequency weighting
- Fast & Slow time weighting
- Record up to 64,000 datapoints and keep track with internal time and date stamp
- User selectable sampling rate from 1 to 60 seconds
- Large, easy-to-read backlit LCD display
- Digital analog bargraph
- Min/Max hold and auto shut off
- Tripod mount for long-term monitoring
- Low battery indicator
- Includes windshield ball, USB cable, PC software, hard carrying case and batteries

Specifications

Measuring Ranges:

Dynamic Range: Accuracy: Resolution: Analog: **Response Time:**

Frequency Range: Frequency Weighting: Time Weighting: Microphone: Digital Analog Bargraph: Display: Backlit Display: Min: Max: Alarm Indicators: Datalogging Capabilities: Real-Time Clock and Date Stamp: Internal Memory: Auto Shut-off: Tripod Mountable: Low Battery Indicator: Power Supply: Output: Battery Life: PC Connectivity: Product Certifications:

Operating Temperature: Storage Temperature: Operating Humidity: Dimensions:

Weight:

30 to 130 dB Low: 30 to 90 dB Med: 50 to 110 dB High: 70 to 130 dB Full: 30 to 130 dB 60 dB (in each range) ±1.4 dB Digital: 0.1 dB 2 dB Digital: 500ms Analog: 50ms 20Hz to 8kHz A. C Fast/Slow (125ms and 1s) 0.5" (12.7mm) electret condenser Yes (30 segment) 4-digit LCD Yes Yes Yes Under and Over (visual on-screen) Yes Yes

Selectable Sampling Rate: Yes (between 1s and 60s) 1mb (64,000 datapoints) Yes (after 30 mins/off) Yes Yes 4 x AAA Batteries Yes (AC/DC) Approx 50 hours USB Software OS Compatibility: Windows XP/Vista/7/8/10/11 CE, IEC 61672-1 Class 2, ANSI S1.4 Type 2 32 to 104°F (0 to 40°C) 14 to 140°F (-10 to 60°C) 10 to 90% 10.4 x 2.5 x 1" (264 x 63 x 29mm) 8.8oz (245g)

Continued...

1.800.561.8187



information@itm.com



Data Logging Sound Level Meter Model R8080



TECHNICAL DATA

R8080-KIT

Data Logging Sound Level Meter & Calibrator Kit



Includes:

R8080 Data Logging Sound Level Meter, R8090 Sound Calibrator, and R8888 Hard Carrying Case with custom foam insert

R8080-KIT2

Data Logging Sound Meter with Tripod Kit

Includes: R8080 Data Logging Sound Level Meter and R1500 Tripod



Model	Description
R8080	Data Logging Sound Level Meter
R8090	Sound Calibrator
REED-WB	Windshield Ball
R1500	Lightweight Tripod
CA-05A	Soft Carrying Case
R8888	Hard Carrying Case
R8080-KIT	Data Logging Sound Level Meter & Calibrator Kit
R8080-KIT2	Data Logging Sound Meter with Tripod Kit
R8080-NIST	Data Logging Sound Level Meter & NIST
R8080-KIT-NIST	Data Logging Sound Level Meter & Calibrator Kit & NIST

1.800.561.8187



information@itm.com