

Video Inspection Camera





Instruction Manual

Table of Contents

Introduction	
Product Quality4	
Safety4-6	
Battery Pack Safety and Using Guide4-5	
Usage Tips5-6	
Features7	
Included7	
Specifications	
Instrument Description9-12	
Camera Head9	
Cable Wheel and Push Cable9	
Battery Pack9	
Remote Control10	
DVR and Tool Box Contents Description11-12	
DVR Icon Description12	
Operating Instructions12-20	
Installation12-14	
Installing Camera Head12-13	
Installing the Support Guide Fitting13	
Installing the 1.8" (46mm) Support Guides13	
Installing the 3.15" (80mm) Support Guides	
Installing the SD Card14	
DVR Function Guide14	
Live Video14	
Video Menu Options14-15	
Setting the Video Resolution	
Set Recording Time	
Enabling/Disabling Sound	
Enabling/Disabling Timestamp15	



Playback Mode16
Playback Settings16-18
Deleting Media Files
Setting Interval Time
Protecting Media Files17
Setting Thumbnail Viewer
File List Viewer
Volume Adjustment
Setup Mode
Formatting the SD Card18-19
Adjusting LCD Brightness
Selecting System Language19
System Reset
Setting Light Frequency
Selecting TV Output
Enabling/Disabling Date & Time
Applications
Accessories and Replacement Parts
Product Care21
Product Warranty21
Product Disposal and Recycling21
Product Support

Introduction

Thank you for purchasing your REED R9000 Video Inspection Camera. Please read the following instructions carefully before using your instrument. By following the steps outlined in this manual your meter will provide years of reliable service.



Product Quality

This product has been calibrated during the manufacturing process to meet the stated product specifications.

Safety

Read all safety warnings and instructions. To reduce the risk of electric shock, fire and/or serious personal injury, follow the warnings and instructions listed below.

- · Save this operation manual for future reference.
- Do not operate this instrument in explosive atmospheres, such as in the presence of flammable liquids, gases, hazardous chemicals, superheated liquid or heavy dust. It may create sparks which may ignite the dust or fumes.
- The camera head and the push cable are waterproof (IP67 rated), however, the battery pack, DVR and connecter cable are not. Do not expose them to water or rain as this increases the risk of electrical shock.
- Never point the connected camera in someone's eyes when the monitor is switched on as the LEDs are bright.
- · Avoid using in environments of extreme cold, heat or humidity.
- Do not store or use the instrument and battery pack in locations where the temperature may reach or exceed 122°F (50°C).
- Do not drop the case as it may damage the instrument.
- Only authorized service centers are allowed to repair this instrument.
- Do not use the camera if condensation forms inside the lens. Let the water evaporate before using again.
- Do not use in places where there is high voltage equipment as it does not contain high voltage protection and isolation.
- Only use attachments/accessories specified by the manufacturer.

Battery Pack Safety and Guide

Read the following battery pack safety precautions before using the battery and charger to reduce the risk of electrical shock.

 Recharge the battery pack with the proper accessory charging unit to avoid any damage.



- Do not charge or use battery in explosive atmospheres, such as in the presence of flammable liquids, gases or dust. Inserting or removing the battery from the charger may ignite the dust or fumes.
- DO NOT splash or immerse in water or other liquids as it will increase the risk of electrical shock.
- Never attempt to open the battery pack. If battery pack case is cracked or damaged, do not insert into charger.
- Never connect the car charger to any 24 volt cigarette lighter slot as it will harm the battery pack and DVR.
- Do not disassemble charger or battery pack; send it to an authorized service center when service or repair is required. Incorrect reassembly may result in electrical shock or fire.
- If the skin comes into contact with battery contents, wash area with mild soap and water. If it gets into the eye, seek immediate medical attention.
- Plug the power adapter to the AC outlet, and insert the other end into the DC inlet located on top of the battery pack. During the charging process, the LED lights will be red and turn to green when fully charged.
 If the battery has been depleted for a long period of time, the charger will pre-charge the battery automatically for approx. 10 minutes, during which time the LED lights will be blink red.
- When the battery pack is turned on it will supply the system and the battery level will be indicated by the green LED indicators. There are 4 indicators and each represents 25% of the battery.
- Allow up to 8 hours to fully charge the battery. If possible, recharge the battery when the camera system is switched off. This increases the operational lifetime of the rechargeable battery.

Usage Tips

- Use a power adaptor or car charger to charge the battery pack.
- If the instrument will not be used for a long period of time, recharge the battery pack every 6 months.
- Always backup your data before connecting your SD memory card to this system.
- Do not disconnect the instrument while recording or during playback as it may damage the instrument and/or the SD memory card.



- Handle the cable with care at all times. The cable is made of a flexible material and can cause a whipping motion when tension is released. It is strongly recommended to protect your eyes with safety glasses during use.
- Suitable for pipes with a diameter of 0.98 to 7.87" (25 to 200mm).
- Ability to go through 90° bends in pipes with a minimum diameter of 1.97" (50mm).
- For health and safety reasons it is strongly recommended to wear rubber gloves when operating the camera.
- Try to keep the push cable away from sharp edges of a pipe as this may cause damage.
- NEVER force the camera through a pipe as this may damage the camera head.
- Always try to run water down the pipe under inspection. This will keep the system clean and allow the camera to be pushed further.
- When the camera has settled in the pipe, adjust the LED lights to a level which provides the best picture.
- It is usually necessary to give a little extra push at changes in direction such as P- traps, Tee's, Y's, Elbows, etc. Pull back the camera head approximately 8" (20cm) from the bend, if necessary, and give it a quick push, "popping" the camera through a turn. Try to be as gentle as possible and do not hammer or snap the camera head through corners.
- Do not try to use the camera head to clear obstructions. This system is a diagnostic tool, not a drain cleaner. Using the camera head to clear obstructions could damage the camera head or cause it to be caught in the pipe.
- If the camera sits in a pipe, or an enclosed environment for long periods of time, heat may buildup. This may lead to the camera head overheating which will cause fuzzy lines to appear on the monitor. In the event this occurs, turn off the system immediately, remove the camera from the pipe and let the camera head cool for 10 to 15 minutes. Running cooler water into the line will also help cool the camera head.
- When the inspection is finished it is recommended to use paper towel or a rag to wipe off the push cable as it is being retrieved.



Features

- Complete video inspection system built in a hard carrying case
- Camera and video functions save high resolution images and records video/audio
- Twelve high visibility LED lights provide illumination in dimly lit environments
- Scratch-resistant sapphire lens and durable stainless steel camera housing
- 65.6ft (20m) cable mounted on cable reel
- High resolution 16:9 7" TFT LCD display
- Video and audio output
- Rechargeable lithium-ion battery and car charger
 Sun visor is included to act as a sun shield for outdoor inspections
- 90° mirror rotation and low battery indicator

Included

Camera Head

Remote Control

- 20m Cable Reel and Push Cable
- Hard Carrying Case with
- built-in DVR
- Battery Pack and Cable
- Car Charger

Fuse

- 1 x Support Guide, 1.8" (46mm)
- 1 x Support Guide, 3.15" (80mm)
- 2 x Screw
- 2 x Nut
- Waterproof Ring and Adapters
- Screwdriver

Specifications

Camera

Camera Resolution: 800 x 480

Camera Diameter: 0.91" (23mm)
Camera Length: 4.7" (120mm)

Lens/Housing Material: Saphire/Stainless Steel

Viewing Distance: 7.9 to 39.4" (20 to 100cm)

Depth of Field: 100cm to infinity

Viewing Angle: 0 to 140°

continued



General Specifications

Display: 7" Color TFT LCD (16 x 9)

Display Resolution: 800 x 480

Frames per Second (FPS): 30

Standard Gooseneck/Cable Length: 65.6' (20m)
Cable Diameter: 0.2" (5.2mm)

Rotate Display: Yes (90°)

Playback: Photo, Video and Audio

Memory: Internal/SD Card

TV Out: PAL/NTSC
Data Output: USB/SD Card

LED Brightness Adjustment: Yes (12 white LEDs)

Low Battery Indicator: Yes

Power Supply: Rechargeable Li-ion Battery, AC Adapter, Car Charger

On-Screen Supported Languages: English, German, French, Spanish,

Italian, Chinese, Japanese,

Russian, Portuguese

Russian, Portuguese

Product Certifications: CE, IP67 (Camera Head)
Operating Temperature: 14 to 122°F (-10 to 50°C)
Storage Temperature: 4 to 140°F (-20 to 60°C)

Operating Humidity Range: 30 to 90%

Dimensions: 22.7 x 10.4 x 20.4"

(575 x 265 x 520 mm)


Weight: 22lbs (10kg)

Instrument Description

The pipe inspection system includes the following four main parts: camera head, cable reel, battery pack and DVR.


Camera Head

- 1. Connector
- 2. Spring
- 3. LED Lights
- 4. Sapphire Lens



Cable Wheel and Push Cable

- 1. Rotation Mechanism
- 2. Cable Wheel
- 3. Push Cable
- Cable Connector (to Camera)
- 5. Handle




Battery Pack

- 1. DC 7.4V Output
- 2. USB Output (DC 5V)
- 3. DC 12V Recharging
- Power Button
- LED (Battery Level Indicator)
- 6. Fuse



Remote Control




- Menu Button 1.
- 2. Pt/Wt: Meter Counter Function (Not Available)
- Up: Select Up/Previous Item 3.
- Left: Select Left Item 4.
- Down: Select Down/ 5. Next Item
- 6. LED: Adjust the LED Brightness

- Photo: Take Photo
- REC: Start/Stop Recording
- Mirror: Mirror And Flip Image
- 10. Right: Select Right Item
- 11. OK & Home: Confirm/ Select Menu
- 12. Exit: Exit Menu
- 13. Playback Button

continued...

10

DVR and Tool Box Contents Description



- 1. Sun Visor
- 2. Color TFT LCD Display
- 3. Playback Mode Button Menu Button
- 4. Pt/Wt: Meter Counter Function (Not Available)
- 5. Menu Button
- 6. Power Indicator LED
- 7. Exit Menu Button
- 8. Left Button
- 9. Down: Select Down/ Next Item
- OK & Home: Confirm/ Select Menu

- LED: Change the LED Brightness
- 12. IR For Remote Control
- 13. REC: Start/Stop Recording
- 14. Power Switch
- 15. Photo: Take Photo
- 16. USB 2.0 to PC
- 17. SD Card Slot
- 18. Mirror: Mirror and Flip Image
- 19. Right: Select Right Item
- 20. Up: Select Up/Previous Item





- 21. Video & Audio Out
- 22. DC In
- 23. DC 12V Cable
- 24. Camera Head Slot
- 25. Battery Pack & Cable
- 26. Remote Control Slot
- 27. Adapter & Car Charger
- 28. Aviation Electrical Connector

Connector

DVR Icon Description

- Record
- 2. LED Brightness
- 3. Timestamp
- 4. Image Mirror
- 5. Image Reverse & Mirror
- 6. Image Reverse
- 7. Battery Level
- 8. SD Card

8 -7 -6 -6 -6 -4 -6 12:34:56 1 2 3

Operating Instructions

Installation


Installing Camera Head

- Prior to installing the camera, ensure the cable is secured on the hook of the handle.
- 2. Hold the cable connector in one hand.
- Grip the guide spring and screw the camera head clockwise until it is tight.
- Ensure the seal ring and the gold pins are in good condition before installing camera head.

continued...



26)






Installing the Support Guide Fitting

Support guides are designed to help position the camera towards the middle of the pipe. Two different size guides are available to meet application requirements.

1. Installing the 1.8" (46mm) Support Guides


With the included screwdriver unscrew the 46mm support guide. Place each part of the guide on either side of the camera head and tighten the screws to fasten the guide.



Applicable to 2.5 to 3.5" pipe

2. Installing the 3.15" (80mm) Support Guides


With the included screwdriver unscrew the 80mm support guide. Place each part of the guide on either side of the camera head and tighten the screws to fasten the guide.



Applicable to 4 to 5" pipe



Installing the SD Card



DVR Function Guide

Live Video

- 1. Press Φ to turn on/off. When powered, the DVR will enter the live video mode. Press (to enter playback mode.
- 2. Press (REC) to start/stop recording.
- 3. Press 1 to mirror and/or reverse the image.
- 4. Press (ED) to adjust the brightness of camera LEDs.
- 5. Press to take a picture.

Video Menu Options

- 1. Press the button to enter the video menu options.
- 2. Press the ▲ and ▼ arrows to scroll through the following parameters:

Setting the Video Resolution (Size)	
Set Recording Time (Video Seg)	
Enabling/Disabling Sound (Sound)	
Enabling/Disabling Timestamp (Timestamp)	

 Once the appropriate parameter has been selected by pressing the button follow the associated instructions below.





Setting the Video Resolution

- Press the ▲ and ▼ arrows to select between "HD", "D1 (720*576)", "VGA (640*480)". "QVGA (320*240)".
- 2. Press the button to confirm the selection.
- Press the (str) button to exit the "Video Menu Options" and resume normal operation.

Set Recording Time

 Press the ▲ and ▼ arrows to select between 10min, 20min, 30min, 40min of recording time or "OFF".

Note: When enabled, this function prevents oversized files and overwrites older files when SD memory card is full. Set to "OFF" to disable file size restriction and overwriting.

- 2. Press the button to confirm the selection.
- Press the (str) button to exit the "Video Menu Options" and resume normal operation.

Enabling/Disabling Sound

- Press the ▲ and ▼ arrows to select between "ON" or "OFF".
- 2. Press the button to confirm the selection.
- 3. Press the (xiii) button to exit the "Video Menu Options" and resume normal operation.

Enabling/Disabling Timestamp

- Press the ▲ and ▼ arrows to select between "Date & Time", "Date only" or "OFF".
- 2. Press the button to confirm the selection.
- 3. Press the $^{\text{(EMT)}}$ button to exit the "Video Menu Options" and resume normal operation.





Playback Mode

Press the () button to enter playback mode, which allows the user to browse, preview and playback media files.

Note: If there are no files to view, the display will indicate "NO IMAGE". Press the (>) button to exit.

- Press the ▲ and ▼ arrows to scroll through media files. 2.
- 3. Press the (button to confirm the selection.
- Follow the media controls below to preview the selected media file: 4.
 - button to Play/Pause media file
 - button to stop the playback and skip back to the beginning
 - d button to rewind the media file
 - button to forward the media file
 - ▼ button set speed rate of rewind/forward function of the media file
- Press the (EXIT) button to exit the selected media file and return to the "Playback" mode.

Note: At any time, you can press the button to exit and resume normal operation.

Playback Settings

- While in playback mode, press the (MENU) button to enter the 1. playback settings.
- 2. Press the ▲ and ▼ arrows to scroll through the following parameters:

Delete	Delete single or all media files
Slide Show	Set interval time of the slide shows ranging from 3sec/5sec/10sec
Protection	Protect important media files
Thumbnail	View 9 media files per page
File List	View 3 media files per page
Volume	Adjust the volume of media files

3. Once the appropriate parameter has been selected by pressing the button follow the associated instructions below.

continued



<u>Deleting Media Files</u>

- Press the ▲ and ▼ arrows to select between deleting a "Single/ Current Media File" or "All Media Files".
- 2. Press the button to confirm the selection.
- Press the (sur) button to exit the Playback settings and return to the Playback mode.

Note: At any time, you can press the button to exit and resume normal operation.

Setting Interval Time

- Press the ▲ and ▼ arrows to select between 3sec/5sec/10sec slide show interval times.
- Press the button to confirm the selection and view selected media file slide show.
- Press the playback settings and return to the Playback mode.

Note: At any time, you can press the button to exit and resume normal operation.

Protecting Media Files

- Press the ▲ and ▼ arrows to select between protecting a "Single/ Current Media File" or "All Media Files".
- 2. Press the button when selected.
- 3. Press the button again to "Set" the media file protection.

Note: Repeat steps 1 to 3 to cancel the protected file(s).

 Press the [str] button to exit the Playback settings and return to the Playback mode.

Note: At any time, you can press the button to exit and resume normal operation.

Setting Thumbnail Viewer

Pressing the button while in playback settings executes thumbnail viewer.

Note: At any time, you can press the button to exit and resume normal operation.





File List Viewer

Pressing the button while in playback settings executes file list viewer.

Note: At any time, you can press the button to exit and resume normal operation.

Volume Adjustment

- Press the ♠ and ▼ arrows to adjust the volume of media file(s) ranging from 4 to 6.
- 2. Press the button to confirm the selection.
- Press the (str) button to exit the Playback settings and return to the Playback mode.

Note: At any time, you can press the button to exit and resume normal operation.

Setup Mode

- 1. Press the (MENU) button to enter the video menu options.
- Press the button to enter setup mode/menu.
- 3. Press the ▲ and ▼ arrows to scroll through the following parameters:

Format	Format the SD card
LCD	LCD brightness
Language	English, German, French, Spanish, Italian, Chinese, Japanese, Russian, Portuguese
System Reset	Reset all settings
Light Frequency	Setting ambient light frequency, 50/60Hz
TV Output	PAL/NTSC
Date Input	To set date and time of media file

 Once the appropriate parameter has been selected by pressing the button follow the associated instructions below.

Formatting the SD card

- 1. Press the \triangle and ∇ arrows to cancel or execute the SD card formatting.
- The system will automatically return to the Setup menu when formatting is complete.



3. Press the [NT] button to exit the "Video Menu Options" and resume normal operation.

Adjusting LCD Brightness

- Press the ▲ and ▼ arrows to adjust the LCD brightness of media file(s) ranging from 7 to 9 intensity.
- 2. Press the button to confirm the selection.
- Press the street button to exit the "Video Menu Options" and resume normal operation.

Selecting System Language

- Press the ▲ and ▼ arrows to select the required system language from the default list.
- 2. Press the button to confirm the selection.
- Press the (ENT) button to exit the "Video Menu Options" and resume normal operation.

System Reset

- 1. Press the ▲ and ▼ arrows to cancel or execute the system reset
- The system will automatically return to the normal operation screen when complete.

Setting Light Frequency

- 1. Press the \triangle and ∇ arrows to select between 50 or 60Hz light frequency.
- 2. Press the button to confirm the selection.
- Press the [str] button to exit the "Video Menu Options" and resume normal operation.

Selecting TV Output

- Press the ▲ and ▼ arrows to select between "NTSC" or "PAL TV" output.
- 2. Press the button to confirm the selection.
- Press the (str) button to exit the "Video Menu Options" and resume normal operation.





Enabling / Disabling Date & Time

- Press the ▲ and ▼ arrows to "Enable (Set)" or "Disable (Off)" media file date & time.
- 2. Press the (button to confirm the selection.
- 3. If enabled, press the ▲ and ▼ arrows to display the date as "DD/MM/YYYY", "MM/DD/YYYY" or "YYYY/MM/DD".
- When selected, press the ◀ and ▶arrows to scroll through each value and adjust if required.
- To adjust a specific value press the ▲ and ▼ arrows.
- 6. Press the button to confirm the timestamp.
- Press the (str) button to exit the "Video Menu Options" and resume normal operation.

Applications

- · Sewer and pipe inspection
- Building ducts/HVAC/R inspections
- Well inspections
- · Building and home inspection

Accessories and Replacement Parts

R9000-BALL Replacement Ball Guide

R9000-SKID Replacement Skid Guide

R9000-RCH Replacement Camera Head

R9000-CAMT Camera head with 512hz Transmitter

R9000-RCV Receiver, 512hz

R9000-20M Replacement 65.6' (20m) Cable

R9000-40M Extended Length Cable 131.2' (40m)

SD-4GB SD Memory Card, 4GB

RSD-16GB Micro SD Memory Card w/Adapter, 16GB

Don't see your part listed here? For a complete list of all accessories and replacement parts visit your product page on www.reedinstruments.com.



Product Care

To keep your instrument in good working order we recommend the following:

- Store your product in a clean, dry place.
- Change the battery as needed.
- If your instrument isn't being used for a period of one month or longer please remove the battery.
- Clean your product and accessories with biodegradable cleaner. Do not spray the cleaner directly on the instrument. Use on external parts only.

Product Warranty

REED Instruments guarantees this instrument to be free of defects in material or workmanship for a period of one (1) year from date of shipment. During the warranty period, REED Instruments will repair or replace, at no charge, products or parts of a product that proves to be defective because of improper material or workmanship, under normal use and maintenance. REED Instruments total liability is limited to repair or replacement of the product. REED Instruments shall not be liable for damages to goods, property, or persons due to improper use or through attempts to utilize the instrument under conditions which exceed the designed capabilities. In order to begin the warranty service process, please contact us by phone at 1-877-849-2127 or by email at info@reedinstruments.com to discuss the claim and determine the appropriate steps to process the warranty.

Product Disposal and Recycling



Please follow local laws and regulations when disposing or recycling your instrument. Your product contains electronic components and must be disposed of separately from standard waste products.



Product Support

If you have any questions on your product, please contact your authorized REED distributor or REED Instruments Customer Service by phone at 1-877-849-2127 or by email at info@reedinstruments.com.

Please visit www.REEDINSTRUMENTS.com for the most up-to-date manuals, datasheets, product guides and software.

Product specifications subject to change without notice.

All rights reserved. Any unauthorized copying or reproduction of this manual is strictly prohibited without prior written permission from REED Instruments.

REED

TEST & MEASURE WITH CONFIDENCE



CHECK OUT OUR LATEST PRODUCTS!

REED



