

HOBO® RG3 Rain Gauge

Rainfall data logging system

The HOBO RG3 data logging rain gauge is a self-contained device that includes an integrated data logger with a high-quality tipping-bucket rain gauge. The RG3's logger has a built-in temperature sensor and is on a cable so it can be used in an optional radiation shield for logging air temperature.

Supported Measurements: Rainfall, Temperature

Key Advantages:

- Aluminum housing and 15.4 cm (6.06 in) collector ring
- · Field-proven design
- Logger can be moved into an optional radiation shield for logging air temperature
- · Three mounting feet to use on flat, level surfaces
- Side bracket for mast mounting (hose clamps included)
- Self-emptying for continuous rainfall logging

Minimum System Requirements:



Software Base Station*







information@itm.com

Part numbers	RG3-M, RG3
Memory	Events only: 16K to 23K events Events and temperature: 25K to 30K data points
Measurement range	Up to 320 cm (RG3-M), up to 160 in (RG3)
Resolution	0.2 mm (RG3-M), 0.01 in (RG3)
Time stamp resolution	1 second
Maximum Rainfall rate	12.7 cm (5 in) per hour
Battery life	1 year typical, user-replaceable, CR2032
	Temperature
Measurement range	-20° to 70°C (-4° to 158°F)
Accuracy	\pm 0.53°C from 0° to 50°C (\pm 0.95°F from 32° to 122°F); a solar radiation shield is required for temperature measurements in sunlight
Resolution	0.14°C at 25°C (0.25°F at 77°F)
Sample rate	1 second to 18 hours, user-selectable
Dimensions	15.2 cm diameter x 25.7 cm high (6 x 10 in) 1.2 kg (2.5 lbs)
CE compliant	Yes

Copyright© 2016 Onset Computer Corporation. All rights reserved. Onset, HOBO, HOBOware are registered trademarks of Onset Computer Corporation. Other products and brand names may be trademarks or registered trademarks of their respective owners. Patented technology (U.S. Patent 6,826,664) MKT1145-0229





information@itm.com