



Features

Model R5010 True RMS Waterproof Digital Multimeter

- True RMS measures frequency, resistance, capacitance and temperature
- Diode check and continuity functions
- Backlit LCD readout with analog bar graph
- 4-20 mA process loop measurements with % readout
- Data hold, Max/Min and Peak capture mode
- IP67 dust and waterproof
- Cat. IV 600V, Cat. III 1000V safety rating

Model R5020 AC Clamp Meter

- Measures AC current, AC/ DC voltage, resistance, capacitance, frequency, duty cycle and temperature
- 4000-count LCD display with low battery and overrange indicators
- Built-in non-contact voltage detector with LED indicator
- Display hold and relative mode
- Diode test and continuity check functions
- Durable double molded plastic housing
- Cat. III 600V safety rating

Model R2300 Infrared Thermometer

- Built-in laser pointer identifies target area
- User selectable °F or °C
- 12:1 distance to spot size ratio
- Digitally adjustable emissivity
- Max and Min readings
- Backlit display
- High and low alarms
- Low battery indication and auto shut off

Model R5110 Non-Contact Voltage Detector

- Suitable for receptacles or against insulated wire
- Double insulated housing for increased safety
- Audible (buzzer) and visual (LED) indicators
- Built-in flashlight
- Pocket clip
- Auto shut off
- Cat. IV 1000V safety rating

Continued...



Model R2990 Thermocouple Adapter

- For use with REED multimeters and clamp meters with contact temperature functionality.
- Measurement accuracy and temperature range are dependent upon probe.

Model TP-01 Type K Thermocouple Wire Probe

- Measurement range: -40 to 482°F (-40 to 250°C)
- For general purpose temperature applications
- Fast response time
- Compatible with Type-K temperature measuring instruments
- 38" (96.5cm) wire length

Model	Description
RINDUST-KIT	Industrial Combo Kit

Model R1000 Safety Test Lead Set, Double Insulated

- Sharp points for piercing insulation
- Stainless steel tips
- Ergonomic comfort grip
- Length: 48" (1.2m), Tip Length: 0.2" (5mm), Probe Length: 6.1" (155mm)
- 1000V, 10A
- CAT III. 1000V and CAT IV. 600V
- CE certified

Model R8890 Hard Carrying Case

- Customizable foam interior
- O-ring creates watertight seal
- Pressure equalization valve
- Double latch & lock system
- Internal dimensions: 14.2 x 10.1 x 4.5" (361 x 257 x 114mm)
- External dimensions: 15.7 x 12.6 x 6.7" (399 x 320 x 170mm)
- Weight: 6lbs (2.72kg)