

SCOUT TKX

Thermal Imaging Monocular



The FLIR Scout TKx is a pocket-sized thermal vision monocular for exploring the outdoors at night and in lowlight conditions. This thermal monocular with an extended battery life reveals your surroundings, allowing you to clearly see people, objects, and animals from more than 90 meters (100 yards) away. The Scout TKx records thermal images or video in multiple color palettes that can enhance viewing, including InstAlertTM—a greyscale palette that adds color to highlight the hottest object in the scene. Simple to use, the Scout TKx is the perfect companion, whether in the countryside or on your own property.



The FLIR Scout TKx helps you stay aware in the dark of night



STAY AWARE, STAY SAFEUse for personal home security at night

- Keep an eye on your property 24/7
- · Search for missing pets, check for predators
- Scan paths, parking spots, and public parks in the dark
- Share thermal video and still images with others



EXPLORE LIKE NEVER BEFORE

Find wildlife, stay aware in the dark

- Clearly view people and animals up to 90 m (100 yds) away
- Lightweight (170 g/6 oz), rugged design withstands bumps and splashes
- Records up to 1000 still images and 4 hours of video to internal memory



GRAB AND GO SIMPLICITY

Starts up in seconds, no training required

- · Single-handed operation
- Simple four-button design and intuitive interface
- Extended 8-hour battery life
- Multiple video color palettes to enhance viewing, including InstAlert™, Graded Fire, and more




SPECIFICATIONS

| Video refresh rate <9 Hz Field of view (h × v) 20° × 16° Shutter Yes Start up <5 seconds Image processing FLIR proprietary Digital Detail Enhancement User Interface Power button On/off Video detection palettes Brightness to toggle through palettes Brightness Brightness (toggle up<>down) Image capture Short press for image capture, long press for video capture Image download USB-C cable Image Presentation and Recording 640 × 480 LCD display Built-in display Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 18.2 Recording Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 18.2 Recording Internal, rechargeable Li-lon cell with the properties of video Power Battery type Internal, rechargeable Li-lon cell Battery type -20°C to 40°C (-4°F to 104°F) Storage temperatu | General | SCOUT TKx |
|---|----------------------------------|---|
| Field of view (h × v) Shutter Shutter Start up Ves Start up Ves Start up Ves Start up Ves FLIR proprietary Digital Detail Enhancement User Interface Power button Video detection palettes Brightness Brightness (toggle up<>down) Short press for image capture, long press for video capture Image download Image Presentation and Recording Built-in display Color palettes Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Storage temperature range Drop 1.2 m (3.93 ft) Physical Weight Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Detector type | 160 × 120 VOx Microbolometer |
| Shutter Start up Sta | Video refresh rate | <9 Hz |
| Start up <5 seconds Image processing User Interface Power button Video detection palettes Brightness Brightness Brightness (toggle up<>down) Image capture Image download Image Presentation and Recording Built-in display Color palettes Becording Becording Battery type Battery type Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Drop Drop Physical Weight Dimensions FLIR proprietary Digital Detail Enhancement FLIR proprietary Digital Detail Enhancement On/off Short press to toggle through palettes Brightness (toggle up<>down) Short press for image capture, long press for video capture USB-C cable USB-C cable Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Internal, rechargeable Li-lon cell Up to 6.5 hours Environmental IP-67, submersible -20°C to 40°C (-4°F to 104°F) -40°C to 60°C (-40°F to 140°F) -1.2 m (3.93 ft) Physical Weight 0.17 kg (0.37 lbs) Dimensions | Field of view (h x v) | 20°×16° |
| Image processing User Interface Power button Video detection palettes Brightness Brightness (toggle up<>down) Image capture Image download Image Presentation and Recording Built-in display Color palettes Battery type Battery type Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Coperating temperature range Drop Physical Weight Dimensions FLIR proprietary Digital Detail Enhancement FLIR proprietary Digital Detail Enhancement On/off Short press to toggle through palettes Brightness (toggle up<>down) Short press for image capture, long press for video capture USB-C cable Brightness (toggle up<>down) Short press for image capture, long press for video capture USB-C cable USB-C cable USB-C cable Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Internal, rechargeable Li-lon cell Up to 6.5 hours Environmental IP-67, submersible -20°C to 40°C (-4°F to 104°F) -40°C to 60°C (-40°F to 140°F) -1.2 m (3.93 ft) Physical Weight 0.17 kg (0.37 lbs) Dimensions | Shutter | Yes |
| User Interface Power button Video detection palettes Brightness Brightness Image capture Image download Image Presentation and Recording Built-in display Color palettes Back Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Drop Drop 1.2 m (3.93 ft) Physical Weight Dimensions On/off Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press for image capture, long peases for video capture USB-C table: Back Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Internal, rechargeable Li-lon cell Up to 6.5 hours Internal, rechargeable Li-lon cell Up to 6.5 hours Physical Up to 6.5 hours Internal, rechargeable Li-lon cell Up to 6.5 hours Inte | Start up | <5 seconds |
| Power button Video detection palettes Brightness Brightness Image capture Image download Image Presentation and Recording Built-in display Color palettes Back Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Built-in display Color palettes Brightness (toggle up<>down) Short press for image capture, long press for video capture USB-C cable USB-C cable USB-C cable USB-C cable Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Butternal, rechargeable Li-lon cell Up to 6.5 hours Environmental Ingress protection rating Operating temperature range Coperating temp | Image processing | FLIR proprietary Digital Detail Enhancement |
| Video detection palettes Brightness Brightness (toggle up<>down) Image capture Image download Image Presentation and Recording Built-in display Color palettes Belectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Drop 1.2 m (3.93 ft) Physical Weight Dimensions Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press to toggle through palettes Brightness (toggle up<>down) Short press for image capture, long press for video capture USB-C cable Beatury, long press for video capture Inage Cable Back Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Salettery Image capture, long press for video capture USB-C cable Beatury Inage Cable Brightness (toggle up<>down) Short press for image capture, long press for up of video Brightness (toggle up<>down) Brightness (toggle up<>down) Brightness (toggle up<>down) Brightness (toggle through press for up to ideo (aptimal) Brightnes (toggle up<>down) Brightnes (toggle up<>down) Brightnes (toggle up<>down) Brightnes (toggle up For the form image capture, long press for up to ideo (aptimal) Brightnes (toggle up For the follow in the fire 1&2 Saletter Image (aptimal) Brightnes (toggle up For the follow in the fire | User Interface | |
| Brightness Brightness (toggle up<>down) Image capture Short press for image capture, long press for video capture Image Presentation and Recording Built-in display 640 × 480 LCD display Color palettes Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Internal, rechargeable Li-lon cell Battery life (operating) Up to 6.5 hours Environmental Ingress protection rating IP-67, submersible Operating temperature range -20°C to 40°C (-4°F to 104°F) Storage temperature range -40°C to 60°C (-40°F to 140°F) Drop 1.2 m (3.93 ft) Physical Weight 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Power button | On/off |
| Image capture Image download Image Presentation and Recording Built-in display Color palettes Recording Beauting type Battery type Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Coperating temperature range Drop Physical Weight Dimensions Short press for image capture, long press for video capture USB-C cable Usg-C cable U | Video detection palettes | Short press to toggle through palettes |
| Image Presentation and Recording Built-in display Color palettes Color palettes Belight in display Color palettes Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Buttery life (operating) Environmental Ingress protection rating Operating temperature range Operating temperature range Storage temperature range Drop 1.2 m (3.93 ft) Physical Weight Out 1 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Brightness | Brightness (toggle up<>down) |
| Image Presentation and Recording Built-in display 640 × 480 LCD display Color palettes Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Recording Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Internal, rechargeable Li-lon cell Battery life (operating) Up to 6.5 hours Environmental IP-67, submersible Operating temperature range -20°C to 40°C (-4°F to 104°F) Storage temperature range -40°C to 60°C (-40°F to 140°F) Drop 1.2 m (3.93 ft) Physical 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Image capture | Short press for image capture, long press for video capture |
| Built-in display Color palettes Color palettes Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Environmental Ingress protection rating Operating temperature range Coperating temperature range Storage temperature range Drop 1.2 m (3.93 ft) Physical Weight O.17 kg (0.37 lbs) Dimensions Storage temperature and (4.0 × 1.5 × 1.5 in) | Image download | USB-C cable |
| Selectable: Black Hot, White Hot, InstAlert™, Rain, Iron, Lava, Color Wheel, Graded Fire 1&2 Snapshot capture and internal storage for up to 1000 images and 4 hours of video Power Battery type Battery life (operating) Battery life (operating) Environmental Ingress protection rating Operating temperature range Operating temperature range Storage temperature range Drop 1.2 m (3.93 ft) Physical Weight O.17 kg (0.37 lbs) Dimensions Snapshot capture and internal storage for up to 1000 images and 4 hours of video Internal, rechargeable Li-lon cell Up to 6.5 hours Internal, rechargeable Li-lon cell Up to 6.5 hours IP-67, submersible Operating temperature range -20°C to 40°C (-4°F to 104°F) -40°C to 60°C (-40°F to 140°F) -1.2 m (3.93 ft) Physical O.17 kg (0.37 lbs) Dimensions | Image Presentation and Recording | |
| Iron, Lava, Color Wheel, Graded Fire 1&2 | Built-in display | 640 × 480 LCD display |
| Images and 4 hours of video | Color palettes | |
| Battery type | Recording | |
| Battery life (operating) Up to 6.5 hours Environmental IP-67, submersible Operating temperature range -20°C to 40°C (-4°F to 104°F) Storage temperature range -40°C to 60°C (-40°F to 140°F) Drop 1.2 m (3.93 ft) Physical Weight 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Power | |
| Environmental IP-67, submersible Ingress protection rating IP-67, submersible Operating temperature range -20°C to 40°C (-4°F to 104°F) Storage temperature range -40°C to 60°C (-40°F to 140°F) Drop 1.2 m (3.93 ft) Physical 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Battery type | Internal, rechargeable Li-lon cell |
| IP-67, submersible | Battery life (operating) | Up to 6.5 hours |
| Operating temperature range -20°C to 40°C (-4°F to 104°F) Storage temperature range -40°C to 60°C (-40°F to 140°F) Drop 1.2 m (3.93 ft) Physical Weight 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Environmental | |
| Storage temperature range | Ingress protection rating | IP-67, submersible |
| Drop 1.2 m (3.93 ft) Physical 0.17 kg (0.37 lbs) Dimensions 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) | Operating temperature range | -20°C to 40°C (-4°F to 104°F) |
| Physical Weight 0.17 kg (0.37 lbs) Dimensions 101 x 38 x 38 mm (4.0 x 1.5 x 1.5 in) | Storage temperature range | -40°C to 60°C (-40°F to 140°F) |
| Weight 0.17 kg (0.37 lbs) Dimensions 101 x 38 x 38 mm (4.0 x 1.5 x 1.5 in) | Drop | 1.2 m (3.93 ft) |
| Dimensions $101 \times 38 \times 38 \text{ mm } (4.0 \times 1.5 \times 1.5 \text{ in})$ | Physical | |
| | Weight | 0.17 kg (0.37 lbs) |
| Package Includes | Dimensions | 101 × 38 × 38 mm (4.0 × 1.5 × 1.5 in) |
| | Package Includes | |

Handheld thermal camera, neck lanyard, USB-C cable, lens cap

Specifications are subject to change without notice.



PALETTE EXAMPLES



InstAlert: The hottest object in the image is colored while everything else is greyscale



Graded Fire 1&2: The hottest things in the image are shown in a gradient of color while everything else is greyscale



Rain: Well-suited for low-contrast scenes

This product is subject to United States export regulations and may require US authorization prior to export, reexport, or transfer to non-US persons or parties. Diversion contrary to US law is prohibited.

©2022 Teledyne FLIR, LLC. All rights reserved.
Revised 12/05/22
Scout TKx_Datasheet-LTR_112022



