

### SG-Ultra Digital Hydrometer/Density Unit



temperature-compensated specific gravity, density, and density-related values. Select from

**Product Overview** 

multiple units of measure to suit your measurement needs or create custom user-defined requirements. Results include sample identification, measurement unit, temperature correction coefficient, instrument identification and date & time. Results can be downloaded to a printer or PC easily. Reliable results appear in just 3 seconds - just immerse the sampling tube, pull the trigger, and read the final result. Trend results with included management software. The SG-Ultra is commonly used for battery testing (lead-acid & Ni-cad), alcohol and food testing, petroleum testing, and other custom density tests.

The SG-Ultra digital hydrometer/density meter offers 99.999% accurate,

#### Advantages

- Accurate 99.999% Accurate
- User-Friendly Compact, lightweight, and allows for one-hand measurement. Large LCD display screen with back-light
- Robust & rugged, comes with protective carrying case. Sustains tough field environments with a sealed housing
- Wireless Communication Infrared data interface for data exchange with a PC and data export to a printer (data transfer accessories included)
- Storage of up to 1100 results including sample ID, measurement unit, temperature correction coefficient, instrument identification, date and time
- The following measuring units are available for selection: Density, Comp. Density, SG (T/T), SG, API, Brix, Alcohol, H2SO4, Baume, Plato, Proof, Concentration
- Reliable CE Compliant and One YearWarranty

| Technical Specifications      |   |  |
|-------------------------------|---|--|
| Measurement Range:            | Density: 0.000 – 2.000 g/cm3<br>Sample Temperature: 0 <sup>1</sup> – 40 °C (32 <sup>1</sup> – 104 °F)<br>Viscosity: 0 – 2,000 mPa |  |
| Accuracy:                     | Density: 0.001 g/cm3<br>Temperature: ±0.2 °C (±0.4 °F)  |  |
| Resolution:                   | 0.0001 g/cm3  |  |
| Minimum Sample Volume:        | 2 mL  |  |
| Communication:                | IrDA Interface  |  |
| Display:                      | Backlit LCD   |  |
| Internal Storage:             | 1100 Results  |  |
| <b>Operating Environment:</b> | 10 – 50 °C (-15 – 122 °F)   |  |
| Power Requirements:           | (2) AAA Batteries   |  |
| Dimensions:                   | 229 x 114 x 64 mm (9 x 4.5 x 2.5 in)  |  |
| Weight:                       | 360 g (2.7 oz)  |  |
| Sample Tube Dimensions:       | 142.875 x 3.175 mm / 5.625 x 1/8 in. Diameter<br>*Custom lengths available  |  |



### **Kit Includes**

- SG-Ultra
- Sample Tube (5.625" x 1/8")
- IrDA Adapters
- SG-Ultra Management Software
- Carrving Case
- User Manual

| (1) Sample must r | ot freeze in the | e measuring cell |
|-------------------|------------------|------------------|
|-------------------|------------------|------------------|

### **Ordering Information**

| Model No. | Description  |
|-----------|--|
| SG-Ultra  | Digital Hydrometer, Data-Logging, Range: 0.0000 – 2.0000 |

## 1.800.561.8187



# information@itm.com