

HOBO[®] U30-NRC Weather Station

Research-grade data logging weather station

This rugged weather station is one of Onset's most durable outdoor environmental monitoring solutions. Users can easily configure the HOBO U30-NRC Weather Station to fit their application needs. Use up to 15 channels to collect environmental data and then upload to HOBOware Pro software for expert analysis.

Supported Measurements: Barometric Pressure, Leaf Wetness, Light Intensity, PAR, Pulse Input, Rainfall , Relative Humidity, Soil Moisture, Solar Radiation, Temperature, Wind Speed & Direction, 4-20mA, Voltage Input



- Rugged double-weatherproof, tamper-proof enclosure
- · Setup is quick and easy with plug-and-play sensors
- · Fast data offload via USB
- · Optional analog inputs with sensor excitation
- · Includes relay that can be activated on user-defined alarm conditions

Minimum System Requirements:









1.800.561.8187 www. com

information@itm.com

¹AC power adapter or solar panel required. For more details, please visit onsetcomp.com

Part number	U30-NRC
Smart-Sensor Inputs	5 or 10
Data Channels	Maximum of 15 (some sensors use more than one data channel)
Smart Sensor Cable Length	100m (323ft) maximum
Alarm Relay	Can be activated, deactivated or pulsed on user-defined sensor alarms.
Logging Interval	1 minute to 18 hours, user-specified
Data Storage Memory	512K bytes local storage in non-volatile flash memory
Environmental Rating	Weatherproof enclosure, NEMA 4x
Operating Range	-40 to 60°C (-40 to 140°F) see battery life
Power	An Onset solar panel (3w, or 6w) or AC adapter is required
Battery Life	3-5 years, 4 volt 10 AHr rechargeable sealed lead acid
Dimensions	17.8 x 11.7 x 19.3 cm (7.0 x 4.6 x 7.6 in)
Weight	2kg (4lbs 10oz)
Local Communication	USB
CE Compliant	Yes





information@itm.com

Copyright[®] 2016 Onset Computer Corporation. All rights reserved. Onset, HOBO, HOBOware are registered trademarks of Onset Computer Corporation. Other products and brand names may be trademarks or registered trademarks of their respective owners. Patented technology (U.S. Patent 6,826,664) MKT1158-0229