



## 1. ELECTRICAL SPECIFICATIONS

Accuracy is calculated as  $\pm$  [% readings + (no. of digits \* resolution)] at 23°C  $\pm$  5°C, relative humidity <60%HR

### TRMS AC/DC phase - neutral / phase - ground voltage, single / three phase systems

Range (V)	Crest factor	Resolution (V)	Accuracy	Input impedance
2.0 ÷ 600.0	$\leq 2$	0.1	$\pm (0.5\%rdg + 2dgt)$	10M $\Omega$

The meter can be connected to external VTs with selectable ratio from 1 to 3000

### TRMS AC/DC phase - phase voltage, three phase systems

Range (V)	Crest factor	Resolution (V)	Accuracy	Input impedance
2.0 ÷ 1000.0	$\leq 2$	0.1	$\pm (0.5\%rdg + 2dgt)$	10M $\Omega$

The meter can be connected to external VTs with selectable ratio from 1 to 3000

### Phase - neutral voltage anomalies, single / three phase systems

Range (V)	Voltage resolution (V)	Voltage accuracy	Time resolution (50/60Hz)	Time accuracy (50/60Hz)
2.0 ÷ 600.0	0.2	$\pm (1.0\%rdg + 2dgt)$	10ms	$\pm 10ms$

Maximum crest factor: 2; the meter can be connected to external VTs with selectable ratio from 1 to 3000

The voltage threshold can be set from  $\pm 1$  to  $\pm 30\%$

### Phase - phase voltage anomalies, three phase systems

Range (V)	Voltage resolution (V)	Voltage accuracy	Time resolution (50/60Hz)	Time accuracy (50/60Hz)
2.0 ÷ 1000.0	0.2	$\pm (1.0\%rdg + 2dgt)$	10ms	$\pm 10ms$

Maximum crest factor: 2; the meter can be connected to external VTs with selectable ratio from 1 to 3000

The voltage threshold can be set from  $\pm 1$  to  $\pm 30\%$

### AC TRMS current with standard STD transducer clamp

Range (mV)	Crest factor	Resolution (mV)	Accuracy (*)	Input impedance	Overload protection
0.0 ÷ 1000.0	$\leq 3$	0.1	$\pm (0.5\%rdg + 0.06\%FS)$	510k $\Omega$	5V

(\*) Accuracy of the transducer excluded ; FS = Full Scale clamp ; current values <0.1%FC are zeroed

### TRMS AC current with flex FlexINT transducer – 300A full scale (\*\*)

Range (A)	Crest factor	Resolution (A)	Accuracy (*)	Input impedance	Overload protection
0.0 ÷ 49.9	$\leq 3$	0.1	$\pm (0.5\%rdg + 0.24\%FS)$	510k $\Omega$	5V
50.0 ÷ 300.0			$\pm (0.5\%rdg + 0.06\%FS)$		

(\*) Accuracy of the transducer excluded ; FS = Full Scale clamp ; current values <1A are zeroed

(\*\*) The 300A range is selectable inside of the instrument

### TRMS AC current with flex FlexINT transducer – 3000A full scale

Range (A)	Crest factor	Resolution (A)	Accuracy (*)	Input impedance	Overload protection
0.0 ÷ 3000.0	$\leq 3$	0.1	$\pm (0.5\%rdg + 0.06\%FS)$	510k $\Omega$	5V

(\*) Accuracy of the transducer excluded ; FS = Full Scale clamp ; current values <5A are zeroed

### Frequency (voltmetric and amperometric inputs)

Range (Hz)	Resolution (Hz)	Accuracy
42.5 ÷ 69.0	0.1	$\pm (0.2\%rdg + 1dgt)$

### Voltage and current harmonics

Order	Resolution (*)	Accuracy
DC ÷ 25 <sup>th</sup>	0.1V / 0.1A	$\pm (5\%rdg + 5dgt)$
26 <sup>th</sup> ÷ 33 <sup>rd</sup>		
34 <sup>th</sup> ÷ 49 <sup>th</sup> (**)		

(\*) Add to the error of correspondent TRMS parameters; (\*\*) Up to 64<sup>th</sup> order in real time visualisation



### Power – Single phase and three phase systems (@ $\cos\phi > 0.5$ , $V_{mis} > 60V$ , STD clamp)

Parameter [W, VAR, VA]	FS clamp	Range [W, VAR, VA]	Accuracy	Resolution [W, VAR, VA]
Active Power Reactive Power Apparent Power	FS $\leq$ 1A	0.0 – 999.9	$\pm (1.0\%rdg + 6dgt)$	0.1
		1.000 – 9.999k		0.001k
	1A < FS $\leq$ 10A	0.000 – 9.999k		0.001k
		10.00 – 99.99k		0.01k
	10A < FS $\leq$ 100A	0.00 – 99.99k		0.01k
		100.0 – 999.9k		0.1k
	100A < FS $\leq$ 3000A	0.0 – 999.9k		0.1k
		1.000 – 9.999M		0.001M

FS = full scale clamp ;  $V_{mis}$  = voltage reference for power measurement

### Energy – Single phase and three phase systems (@ $\cos\phi > 0.5$ , $V_{mis} > 60V$ , STD clamp)

Parameter [Wh, VARh, VAh]	FS clamp	Range [Wh, VARh, VAh]	Accuracy	Resolution [Wh, VARh, VAh]
Active Energy Reactive Energy Apparent Energy	FS $\leq$ 1A	0.0 – 999.9	$\pm (1.0\%rdg + 6dgt)$	0.1
		1.000 – 9.999k		0.001k
	1A < FS $\leq$ 10A	0.000 – 9.999k		0.001k
		10.00 – 99.99k		0.01k
	10A < FS $\leq$ 100A	0.00 – 99.99k		0.01k
		100.0 – 999.9k		0.1k
	100A < FS $\leq$ 3000A	0.0 – 999.9k		0.1k
		1.000 – 9.999M		0.001M

FS = full scale clamp ;  $V_{mis}$  = voltage reference for power measurement

### Power factor ( $\cos\phi$ )

Range	Resolution	Accuracy
0.20 ÷ 0.50	0.01	1.0
0.50 ÷ 0.80		0.7
0.80 ÷ 1.00		0.6



## 2. GENERAL SPECIFICATIONS

### DISPLAY:

Features:	graphic TFT with backlight, ¼ VGA (320 x 240)
Touch screen:	present
Colours:	64K
Contrast:	adjustable

### POWER SUPPLY:

Internal power supply:	Li-ION, 3.7V rechargeable battery
Battery life:	> 6 hours
External power supplier:	AC/DC adapter 100-240V 50/60Hz / 5VDC
Auto Power Off:	after 5 minutes of idleness (no external power)

### MEMORY AND PC INTERFACE

Every parameter can be stored into the memory. The instrument saves the MIN, AVG and MAX values of the parameters each integration period which can be: 1, 2, 5, 10, 30 seconds, 1, 2, 5, 10, 15, 30, 60 minutes

Maximum parameters to be stored:	251
Memory:	> 3 months @ 251 parameters and integration period = 15 min
Internal memory:	15 Mbyte
External memory:	USB pen drive
External memory:	compact flash card
Operative system:	Windows CE
PC communication port:	USB

The instrument can store **SIMULTANEOUSLY** all the parameters like:

- voltages, currents, power factors, powers, energies, etc.
- ingoing and outgoing power
- voltage anomalies
- voltage and current harmonics
- voltage unbalance

### MECHANICAL FEATURES

Dimensions (L x W x H):	235 x 165 x 75mm
Weight (batteries included):	1.0 kg

### ENVIRONMENTAL CONDITIONS:

Reference temperature:	23°C ± 5°C
Working temperature:	0°C ÷ 40°C
Working humidity:	<80%RH
Storage temperature (batt. not included):	-10°C ÷ 60°C
Storage humidity:	<80%RH

### GENERAL REFERENCE STANDARDS:

Safety:	IEC/EN61010-1, IEC/EN61010-031, IEC/EN61010-2-032
EMC :	IEC/EN61326-1
Insulation:	double insulation
Pollution degree:	2
Overvoltage category:	CAT IV 600V to ground, max 1000V between inputs
Max height of use:	2000m
Harmonics:	IEC/EN61000-4-30 Class B, IEC/EN50160
Unbalance:	IEC/EN61000-4-30 Class B, IEC/EN50160

**This instrument complies with the requirements of the European Low Voltage Directives 2014/35/EU (LVD) and EMC 2014/30/EU**

**This instrument satisfies the requirements of 2011/65/EU (RoHS) directive and 2012/19/EU (WEEE) directive**