

M2000 Series Smart Manometer



Meriam M2000 is a portable pressure instrument with flexible features to meet many of your everyday pressure measurement needs. This device features an easy and intuitive user interface with convenient pressure connections.

Meriam Tethered Sensor (optional accessory)



- 316SS media isolated pressure sensors to suit a wide range of applications
- Common features include damping to stabilize fluctuating pressure signals and data logging for easy measurement capture
- This device ships with calibration certificate traceable to NIST
- M2000 can use a second sensor with the MTS Series of Tethered Modules (Pressure & Temperature)
- **Intrinsically Safe options available**

Features on M2000

- Mobile data logging - no computer required while taking measurements
- meriSuite application for configuration, calibration, and data logging
- One (1) fixed sensor
- Backlight with 4 levels: Off, Low, Medium, High
- Battery life display (0 % to 100%)
- USB communication
- Measure ranges up to: 3000 psi compound, 1000 psi absolute, and 500 psi differential
- Min/Max pressure capture
- RTD (Temperature) accessory sensor option with MTS
- Protective red boot
- Optional pressure fittings, hand pump kit, and carrying case
- UL Listed

Meriam Tethered Sensors (MTS)

Expand the capabilities of the M2000 by adding an MTS to measure a second pressure or a PT100 Class A RTD temperature.

Choose any available pressure or temperature sensor type and range and connect your accessory MTS using the included 1 meter cable.

This is an interchangeable sensor giving extra flexibility to your measurement needs.

Applications

- Pressure Transmitter Calibration
- Leak testing for low pressure gas systems
- Pressure drop monitoring across filters
- Monitoring vacuum on condensers and pumps
- Pressure relief valve testing
- Hold function to snapshot pressure reading


meriSuite CG

Our meriSuite CG application is included with the M2000 so you can configure M2000 and MTS to streamline your daily measurement tasks.

Configure the Smart Manometer and sensors

Configure and download data logs, select measurement units and configure user defined units, turn on and off device functions, and calibrate your device using your local measurement standards.

Add Data Log Pro to the M2000 and MTS to expand data logging capabilities to 128 log files or 100,000 data points. Modify data log options and settings using Data Log Pro tab in meriSuite CG - available with optional MTS.



Specifications M2000 Smart Manometer

Pressure Accuracy	<ul style="list-style-type: none"> ± 0.020% Full Scale + 0.005% of Reading
Pressure ranges (select one)	<ul style="list-style-type: none"> Compatible with clean, dry, non-corrosive, gas media 0 to 15, 30, 100 psi Absolute -1 to 1, -5 to 5, -14.5 to 15, 30, 50, 100 psi Differential -1 to 1, -5 to 5, -14.5 to 15, 30, 50, 100 psi Compound
Non-isolated	
Media-isolated	<ul style="list-style-type: none"> Gas and Liquid Media compatible with 316SS 0 to 15, 30, 100, 1000 psi Absolute -1 to 1, -5 to 5, -14.5 to 15, 30, 50, 100, 300, 500 psi Differential -14.5 to 15, 30, 50, 100, 300, 500, 1000, 3000 psi Compound
Measurement Units	<ul style="list-style-type: none"> Offering over 30 measurement units including psi, kPa, mmHg, inH₂O, mbar, and user defined units - available with optional MTS
Display Resolution	<ul style="list-style-type: none"> Up to 6 digits depending on pressure unit selected
Temperature Specifications	<ul style="list-style-type: none"> Storage: -20 °C to 70 °C (-4 °F to 158 °F) Operating: -10 °C to 50 °C (14 °F to 122 °F)
Dimensions with boot	<ul style="list-style-type: none"> Length 9.8 in (248.9 mm) from manifold to end of boot Width 5.2 in (132.1 mm) at widest point with boot Thickness 2.3 in (58.4 mm)
Connections	<ul style="list-style-type: none"> 1/8" Female NPT 316SS USB Meriam Tethered Sensor (MTS) Port USB
Power	<ul style="list-style-type: none"> 4 AA batteries
MTS RTD Specifications	<p>Temperature Probe Accuracy</p> <ul style="list-style-type: none"> IEC 60751 PT100 class A Tolerance = ± (0.15 + 0.002 t) °C Probe measurement range: -50 °C to 250 °C